


Frank Zulski
Wade Williams
Jim Kargol
Brent Shank, PE
Engineer-Manager
Lisa Kleeman
Finance Director



2265 E. Hathaway Road
Harbor Springs, MI 49740
Office: (231) 347-8142
Fax: (231) 347-5787
www.emmetcrc.org

Project: **US-31 Eppler Culvert Lining**

Culvert Rehabilitation at US-31, West of Eppler Rd, Includes Culvert Lining and Maintenance of Traffic.

The Emmet County Road Commission will accept Bids until **9:00 a.m.** local time on **January 6, 2026** at: 2265 E. Hathaway Road, Harbor Springs, MI 49740. Bid packages are available at the Emmet County Road Commission Office or on Emmet County Road Commission website at www.emmetcrc.org.

**ALL BIDS WILL BE SEALED AND PLAINLY MARKED AS TO THE PROJECT AND PROJECT NUMBER.
MAILED BIDS MUST BE RECEIVED BY 3:30 P.M. THE PREVIOUS EMMET COUNTY ROAD
COMMISSION BUSINESS DAY PRIOR TO BID OPENING.**

The bidder has examined the plans, specification, special provisions and related materials in the proposal, as well as the location of the work described in the proposal for this project, and is fully informed as to the nature of the work and conditions relating to its performance and understands that the quantities shown are approximate only and are subject to either increase or decrease.

The bidder hereby proposes to furnish all necessary machinery, tools, apparatus and other means of construction, do all the work, furnish all the materials except as otherwise specified and, or each unit price, lump sum, or one each named in the itemized bid, to complete the work in strict conformity with the plans therefore and the entire proposal which is incorporated by reference in these pages, and in strict conformity with the requirements of the 2020 Standard Specifications for Construction, Michigan Department of Transportation and such other special provisions and supplemental specifications as may be part of the proposal for this project.

The bidder further proposes to do such extra work as may be authorized by the Emmet County Road Commission, prices for which are not included in the itemized bid. Compensation shall be made on the basis agreed upon before such extra work is begun.

THE BIDDER UNDERSTANDS AND AGREES THAT THE EMMET COUNTY ROAD COMMISSION RESERVES THE RIGHT TO REJECT ANY AND ALL BIDS; TO WAIVE IRREGULARITIES OR INFORMALITIES; AND NO CONTRACTUAL RELATIONSHIP SHALL EXIST BETWEEN THE BIDDER AND THE EMMET COUNTY ROAD COMMISSION FOR THE WORK DESCRIBED HEREIN UNTIL SUCH TIME AS THE CONTRACT HAS BEEN FORMALLY EXECUTED BY BOTH THE BIDDER AND THE EMMET COUNTY ROAD COMMISSION.

The Emmet County Road Commission, in accordance with Title VI of the Civil Rights Act of 1964, 78 Stat. 252, 42 U.S.C 2000d to 2000d-4 and Title 49, Code of Federal Regulations, Department of Transportation, Subtitle A, Office the Secretary, Part 21, Nondiscrimination in Federally assisted programs of the Department of Transportation issued pursuant to such Act, hereby notifies all bidders that it will affirmatively insure that in any contact entered into pursuant to this advertisement, minority business enterprises will be afforded full opportunity to submit bids in response to this invitation and will not be discriminated against on the grounds of race, color, or national origin in consideration for an award.

PROGRESS CLAUSE: Submit a Progress Schedule.

After award, start work on the date approved by the Engineer, which must be no earlier than **March 30, 2026**. In no case may any work be commenced prior to award by the Department.

The entire project must be completed by the final completion date of **May 29, 2026**.

This is an expedited project. The Contractor is responsible to provide sufficient resources and adjust work schedules to complete work within the contract time.

Failure by the Contractor to meet interim completion, open to traffic, and/or final completion dates will result in the assessment of liquidated damages in accordance with subsections 108.10.C.1 and 108.10.C.2 of the Standard Specifications for Construction. Liquidated damages will be assessed separately and simultaneously for failure to meet interim completion, open to traffic, and/or final completion dates. Liquidated damages will continue to be assessed for each calendar day that the work associated with the interim completion, open to traffic, and/or final completion dates remains incomplete, even if these days extend into or beyond seasonal suspension, unless approved otherwise by the Engineer.

Unless specific pay items are provided in the contract any extra costs incurred by the Contractor due to cold-weather protection and winter grading will not be paid for separately but will be included in the payment of other pay items in the contract.

After award and prior to the start of work, the Contractor must attend a preconstruction meeting with the Engineer. The Engineer will determine the day, time, and place for the preconstruction meeting. The meeting will be conducted after project award and may be rescheduled if there are delays in the award of the project. The named subcontractor(s) for, Designated and/or Specialty Items, as shown in the proposal, is(are) recommended to be at the preconstruction meeting if such items materially affect the work schedule.

The Contractor may be required to meet with Department representatives for a post-construction review meeting, as directed by the Engineer. The Engineer will schedule the meeting.

MICHIGAN
DEPARTMENT OF TRANSPORTATION

SPECIAL PROVISION
FOR
MAINTAINING TRAFFIC

GLD:AWK

1 of 6

APPR:BGS:12:9:25

a. Description. This special provision consists of requirements and restrictions to maintain traffic for Job Number 217211 on US-31 in the City of Petoskey and Resort Township, Emmet County.

b. General. Maintain traffic throughout the project in accordance with the standard specifications, typicals, and supplemental specifications in the contract and as described on the plans for this project.

c. Construction Influence Area (CIA). The CIA includes the right-of-way of the following roadways, within the approximate limits described below:

1. On US-31 from approximately ½ mile east and west of the Eppler Road intersection.
2. In addition, the CIA includes the right-of-way of any designated detour route or alternate route, intersecting roads and ramps adjacent to the work zone for a distance of approximately 1/4 mile in advance of the work zone or as far as the construction or detour signing extends. The roads include but are not limited to Eppler Road.

d. Traffic Restrictions. Maintain traffic in accordance with the Maintaining Traffic Typical contained herein, except as noted below. Changes or adjustments to the Maintaining Traffic Typical may be necessary to fit field conditions, subject to approval of the Engineer or as determined by the Engineer.

1. Utilize the following Maintaining Traffic Typicals:

- A. 100-GEN-KEY
- B. 101-GEN-SPACING-CHARTS
- C. 102-GEN-NOTES
- D. 103-GEN-SIGN
- E. 104-GEN-AB
- F. 122-NFW-SHL-(R)
- G. WZD-100-A
- H. WZD-125-E

2. Do not deliver material, or close lanes during the holiday periods as defined in Table 1.

Table 1: 2026 Holiday Periods

| Holiday | Start Date and Time | End Date and Time |
|------------------|--|---|
| Memorial Day | 3:00 pm, Thursday, May 21 st | 6:00 am, Tuesday, May 26 th |
| Independence Day | 3:00 pm, Thursday, July 2 nd | 6:00 am, Tuesday, July 7 th |
| Labor Day | 3:00 pm, Thursday, September 3 rd | 6:00 am, Wednesday, September 9 th |

3. Do not deliver material, or close lanes during the Special Event as defined in Table 2.

Table 2: 2026 Special Event

| Local Event | Start Dates and Time | End Date and Time |
|------------------------------|--|--|
| Emmet-Charlevoix County Fair | 6:00 am, Monday, August 24 th | 6:00 a.m., Monday, August 31 st |

4. Perform work and lane closures within the allowable time frames as shown in Tables 1, 2, and 3, unless otherwise approved by the Engineer.

Table 3: US-31 Northbound Traffic Restrictions

| Closure Type | Start Time | End Time | M | Tu | W | Th | F | Sa | Su |
|-------------------------|------------|----------|---|----|---|----|---|----|----|
| Shoulder Closures | 00:00 | 24:00 | ∞ | ∞ | ∞ | ∞ | ∞ | ∞ | ∞ |
| Right Turn Lane Closure | 00:00 | 24:00 | ∞ | ∞ | ∞ | ∞ | ∞ | ∞ | ∞ |

∞ = half hour before sunrise as defined by the [National Oceanic and Atmospheric Administration \(NOAA\)](#)
 ▼ = half hour after sunset as defined by [NOAA](#)
 ∞ = Closure is allowed, and the frequency is not limited during the project timeframe
 # = The number of times closures can take place during the project timeframe.

5. Maintain a minimum of one lane of traffic in each direction at all times on US-31 and all intersecting roads. No closures of thru lanes, the southbound shoulder, or the center left turn lane will be allowed.

6. No more than one right turn lane/shoulder closure is allowed at a time.

A. The maximum closure length is 1/2 mile unless otherwise approved by the Engineer.

7. When a lane is closed, place channelizing devices at cross streets and major drives to form a radius that clearly defines the approaches to the through and turning traffic.

8. Maintain access to all driveways along US-31 and Eppler Road as directed by the Engineer unless prior agreements are made with the respective property owners. The cost of constructing driveways part width will not be paid for separately but will be considered included in the cost of other driveway pay items.

e. Traffic General.

1. For any lane open to traffic, provide a minimum lane width of 12 feet with 2 feet of shy distance on both sides unless identified otherwise on plans.
2. Do not close lanes or utilize traffic regulation sequences where work can be accomplished with a shoulder closure. Do not occupy any part of the active traffic lane with personnel or equipment when utilizing a shoulder closure. Place lane closures only in areas as shown on the plans unless otherwise directed by the Engineer.
3. Prior to shifting traffic onto shoulders or opening any lanes/shoulders and/or ramps, remove, by sweeping all accumulated debris that has collected within the shoulder and/or within the closed lane/shoulder.
4. Utilize a 40 mph advisory speed when closing the northbound shoulder/right turn lane.
5. Develop and submit to the Engineer an Internal Traffic Control Plan (ITCP) per subsection 104.11.B of the Standard Specifications for Construction. The requirements listed herein are the requirements for a Type A ITCP. Submit the Type A ITCP at the preconstruction meeting. The Engineer will have 7 calendar days to review the ITCP for approval or provide comments for revisions required to obtain approval. Include in the ITCP, at a minimum, the proposed ingress/egress locations for construction equipment and vehicles, traffic control devices that will be utilized to warn the motoring public of ingress/egress locations, and measures that will be taken to ensure compliance with the ITCP. Ensure that the ITCP minimizes conflicts between construction vehicles and motorists and maintains overall safety and mobility within the work zone. No work may begin prior to approval of the ITCP. Additional time required to obtain an approved ITCP will not be cause for delay or impact claims. All costs associated with obtaining an approved ITCP, providing and executing all parts of the approved ITCP including required traffic control devices, or resolving an incomplete or unacceptable ITCP will be borne by the Contractor.
6. Protect the work area at the end of each day. Close all open access points on the project to traffic with Type III barricades or other devices approved by the Engineer.
7. The Engineer will be responsible for notifying emergency services, transit agencies, law enforcement and schools prior to any lane closures, detours or major traffic shifts. In addition, the Contractor will be responsible for working with and complying with any coordination that is necessary with the Department and emergency services, transit agencies, law enforcement and schools. All costs associated with these coordination efforts will be considered included in the pay item "Minor Traf Devices".
8. Obtain all necessary permits from local governments within areas of local jurisdiction, including noise/dust ordinance waivers when required, prior to placing construction signing on local roads.
 - A. Prior to placing construction signing on local roads, obtain an approved permit from the Road Commission for Emmet County and any local agencies. The MDOT Gaylord TSC has submitted the permit application, however the Contractor is responsible for providing the required information to obtain a final approved permit.

9. Remove all temporary traffic control devices from MDOT right-of-way during any shut down periods unless needed for directly maintaining or channelizing traffic. No additional payment will be made for removal and/or redeployment of these devices except for in the case of an approved extension of time.

10. Cover or remove construction signing that refers to work zone speed when work at a location is planned to be inactive for a period greater than 2 days, unless otherwise specified on the plans or as directed by the Engineer.

11. Once work is initiated that includes any lane restrictions, that work must be continued daily until completed. A lack of work activity for more than 3 days will require the removal of lane closures at no expense to the Department.

f. Stage Construction. Maintain traffic in accordance with the restrictions listed in section d. Traffic Restrictions and the sequence of operations contained herein. Use of an alternate traffic control plan is subject to review and approval by the Engineer.

1. Stage 1.

A. Construction

(1) Structural crack repair, hand chipping, and apply geopolymers structural liner on the culvert under US-31.

B. Traffic Control and Restrictions

(1) Close the northbound US-31 shoulder and the northbound US-31 right turn lane to southbound Eppler Road.

(2) Maintain pedestrian and non-motorized access to the Little Traverse Wheelway and southbound US-31 shoulder.

g. Pedestrian or Non-Motorized Facilities.

1. Maintain all facilities in accordance with *The Americans with Disability Act (ADA)* requirements and the Public Rights-of Way Accessibility Guidelines (PROWAG). Provide facilities equivalent to or better than the route a person would have encountered prior to construction activities.

2. Always keep sidewalk areas clear of any equipment or materials when the sidewalks are open to pedestrian traffic. When open to pedestrian traffic, maintain a 4 foot clear path on all sidewalks.

3. Keep the southbound US-31 shoulder clear and open at all times to accommodate non-motorized traffic that may be navigating around the Little Traverse Wheelway closure.

4. At the trail closure points, place pedestrian barricades and R9-9 MOD "TRAIL CLOSED" signs, as directed by the Engineer.

5. On the western end of Lake Street (Magnus Park) and the City of Petoskey Waste Water Sewer Plant, place barricades and W20-9 MOD "TRAIL CLOSED AHEAD" signs to warn trail users of the closures ahead, as directed by the Engineer.

h. Traffic Control Devices. Ensure all traffic control devices are in accordance with the MMUTCD and must meet the "acceptable" criteria as defined in the ATSSA publication entitled "Quality Guidelines for Temporary Traffic Control Devices and Features" at the time of initial deployment and after each major stage change.

1. During non-working periods, place applicable advance signs and channelizing devices at specific locations, as directed by the Engineer, at no additional cost to the Department.

2. Notify the Engineer 24 hours in advance of when traffic control devices are being delivered to the project site, to allow for initial inspection of devices to take place.

3. Remove from the project site all traffic control devices (including detour signing) no longer needed for a particular operation and equipment for construction within 14 calendar days of reopening the shoulder/lane/roadway.

4. Channelizing Devices.

A. Ensure all devices have sufficient ballast to prevent moving or tipping. If moving or tipping occurs, place additional ballast, as directed by the Engineer, at no additional cost to the Department. No more than two ballasts are allowed on each channelizing device.

B. Do not use caution tape on channelizing devices for traffic control and/or pedestrian traffic control on this project.

C. Space channelizing devices at 25 feet for tapers and 25 feet for tangents or tighter as directed by the Engineer.

5. Temporary Signs.

A. Additional W20-1 (ROAD WORK AHEAD) signs are included in the quantities to be placed on all intersecting or adjacent roads where construction activities may be encountered.

B. Fabricate, install, and remove temporary sign overlays on existing signs with the pay item for Sign, Type B, Temp, Prismatic, Furn. Attach the overlay in accordance with subsection 812.03.D.2 of the Standard Specifications for Construction.

C. Place five R3-2 "No Left Turn" (30"x30") and R3-2 MOD "AT US-31" (30"x12") signs on Eppler Rd in advance of US-31, as directed by the Engineer.

i. Measurement and Payment. Payment will be in accordance with the standard specifications unless otherwise specified. No additional payment will be made for the following activities:

1. Transporting traffic control items from site to site.


2. Providing sufficient vehicles and staff to make changes as-needed on site during work.
3. Providing sufficient vehicles and staff to remove closures from the roadway.

TYPICAL NUMBER KEY

CODES

| |
|-----------------------------|
| AB = ARROW BOARD |
| AW = ADVANCE WARNING |
| C = CLOSURE |
| CLT = CENTER LEFT TURN LANE |
| CROSS = CROSSOVER |
| CruSha = CRUSH AND SHAPE |
| EM = EARLY MERGE |
| EnR = ENTRANCE RAMP |
| ExR = EXIT RAMP |
| FW = FREEWAY |
| GEN = GENERAL INFORMATION |
| GORE = FREEWAY GORE AREA |
| IN = INSIDE |
| INT = INTERSECTION |
| L = LANE |
| (L) = LEFT |
| LC = LANE CLOSURE |
| LD = LONG DURATION |

| |
|---|
| LO = LANE OPEN |
| O = OUTSIDE (LANE CLOSURE) |
| OUT = OUTSIDE OF SHOULDER |
| MID = MIDDLE OF INTERSECTION OR ROAD |
| NFW = NON-FREEWAY |
| PARK = PARKING LANE |
| PCMS = PORTABLE CHANGEABLE MESSAGE SIGN |
| (R) = RIGHT |
| ROLL = ROLLING ROADBLOCK |
| RUM = RUMBLE STRIP |
| SD = SHORT DURATION |
| SHL = SHOULDER CLOSURE |
| SIGN = SIGN |
| SP = SPECIAL |
| SPEED = SPEED |
| STA = STOPPED TRAFFIC ADVISORY |
| TR = TRAFFIC REGULATOR |
| TS = TEMPORARY SIGNAL |
| ZIP = ZIPPER MERGE |



| |
|------------------------------------|
| 100 - GENERAL NOTES |
| 110 - TRAFFIC REGULATORS |
| 120 - NON-FREEWAY |
| 130 - CENTER LEFT TURN (CLT) LANES |
| 140 - PARKING LANES |
| 150 - CLT 7 LANE SECTIONS |
| 160 - SIGNAL WORK |
| 200 - FREEWAY CLOSURES |
| 210 - FREEWAY LANE SHIFTS |
| 220 - FREEWAY ENTRANCE RAMPS |
| 230 - FREEWAY EXIT RAMPS |
| 300 - ADVANCE WARNINGS |
| 310 - CROSSOVER CLOSURE |
| 320 - CRUSH AND SHAPE |
| 340 - MERGE SYSTEMS |
| 350 - GORE LOCATIONS |
| 360 - ROLLING ROADBLOCK |
| 4000 - MAINTENANCE |
| 5000 - SURVEY |

EXAMPLE TYPICAL

CODE: 152-CTL(7)-3(1R+2L)LC-2(L)SHIFT

152 - TYPICAL NUMBER

CTL(7) = CENTER LEFT TURN LANE, 7 LANES TOTAL.

3(1R+2L)LC = 3 LANES CLOSED, (1 RIGHT LANE AND 2 LEFT LANES).

2(L)SHIFT = 2 LANES SHIFTED TO THE LEFT.

NOT TO SCALE



NOT TO SCALE

MAINTAINING TRAFFIC TYPICAL

NO:

100-GEN-KEY

TYPICAL NUMBERING KEY

DATE: DECEMBER 2021
SHEET:

1 OF 1

FILE: 100-GEN-KEY.dgn

DISTANCE BETWEEN TRAFFIC SIGNS, "D"

| "D" DISTANCES | POSTED SPEED LIMIT, MPH (PRIOR TO WORK AREA) | | | | | | | | | | |
|------------------|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 |
| D (FEET) | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 | 650 | 700 | 750 |

GUIDELINES FOR LENGTH OF LONGITUDINAL BUFFER SPACE, "B"

| "B" LENGTHS | SPEED*, MPH (PRIOR TO WORK AREA) | | | | | | | | | | | |
|----------------|----------------------------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 |
| B (FEET) | 33 | 50 | 83 | 132 | 181 | 230 | 279 | 329 | 411 | 476 | 542 | 625 |

* POSTED SPEED, OFF-PEAK 85TH PERCENTILE SPEED PRIOR TO WORK STARTING, OR THE ANTICIPATED OPERATING SPEED.

MINIMUM MERGING TAPER LENGTH, "L" (FEET)

| OFFSET (FEET) | POSTED SPEED LIMIT, MPH (PRIOR TO WORK AREA) | | | | | | | | | | |
|------------------|--|-----|-----|-----|-----|-----|-----|-----|-----|------|------|
| | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 |
| 1 | 11 | 15 | 21 | 27 | 45 | 50 | 55 | 60 | 65 | 70 | 75 |
| 2 | 21 | 30 | 41 | 54 | 90 | 100 | 110 | 120 | 130 | 140 | 150 |
| 3 | 32 | 45 | 62 | 80 | 135 | 150 | 165 | 180 | 195 | 210 | 225 |
| 4 | 42 | 60 | 82 | 107 | 180 | 200 | 220 | 240 | 260 | 280 | 300 |
| 5 | 53 | 75 | 103 | 134 | 225 | 250 | 275 | 300 | 325 | 350 | 375 |
| 6 | 63 | 90 | 123 | 160 | 270 | 300 | 330 | 360 | 390 | 420 | 450 |
| 7 | 73 | 105 | 143 | 187 | 315 | 350 | 385 | 420 | 455 | 490 | 525 |
| 8 | 84 | 120 | 164 | 214 | 360 | 400 | 440 | 480 | 520 | 560 | 600 |
| 9 | 94 | 135 | 184 | 240 | 405 | 450 | 495 | 540 | 585 | 630 | 675 |
| 10 | 105 | 150 | 205 | 267 | 450 | 500 | 550 | 600 | 650 | 700 | 750 |
| 11 | 115 | 165 | 225 | 294 | 495 | 550 | 605 | 660 | 715 | 770 | 825 |
| 12 | 125 | 180 | 245 | 320 | 540 | 600 | 660 | 720 | 780 | 840 | 900 |
| 13 | 136 | 195 | 266 | 347 | 585 | 650 | 715 | 780 | 845 | 910 | 975 |
| 14 | 146 | 210 | 286 | 374 | 630 | 700 | 770 | 840 | 910 | 980 | 1050 |
| 15 | 157 | 225 | 307 | 400 | 675 | 750 | 825 | 900 | 975 | 1050 | 1125 |

NOT TO SCALE



NOT TO SCALE

FILE: 101-GEN-SPACING-CHARTS.dgn

MAINTAINING TRAFFIC TYPICAL

NO: 101-GEN-
SPACING-CHARTS

"B", "D" AND "L" TABLES
CHANNELIZING DEVICE SPACING,
SIGN BORDER KEY, AND ROLL-AHEAD SPACING

DATE: MAY 2021

SHEET:

1 OF 3

THE FORMULAS FOR THE MINIMUM LENGTH OF A MERGING TAPER IN DERIVING THE "L" VALUES SHOWN IN THE ABOVE TABLES ARE AS FOLLOWS:

$$"L" = \frac{W \times S^2}{60} \quad \text{WHERE POSTED SPEED PRIOR TO THE WORK AREA IS 40 MPH OR LESS}$$

$$"L" = W \times S \quad \text{WHERE POSTED SPEED PRIOR TO THE WORK AREA IS 45 MPH OR GREATER}$$

L = MINIMUM LENGTH OF MERGING TAPER

S = POSTED SPEED LIMIT IN MPH PRIOR TO WORK AREA

W = WIDTH OF OFFSET

TYPES OF TAPERS

UPSTREAM TAPERS

MERGING TAPER

SHIFTING TAPER

SHOULDER TAPER

2 TO 1 LANE ROAD TAPER

TAPER LENGTH

L - MINIMUM

1/2 L - MINIMUM

1/3 L - MINIMUM

100' - MAXIMUM

DOWNSTREAM TAPERS

(USE IS RECOMMENDED)

100' (PER LANE)

MAXIMUM SPACING FOR CHANNELIZING DEVICES

| WORK ZONE SPEED LIMIT | DRUM AND 42" DEVICE SPACING (FT) | | NIGHTTIME 42" DEVICE SPACING (FT) | |
|--------------------------|----------------------------------|-----------------|-----------------------------------|---------|
| | TAPER | TANGENT | TAPER | TANGENT |
| < 45 MPH | 1 x SPEED LIMIT | 2 x SPEED LIMIT | 25 FEET | 50 FEET |
| ≥ 45 MPH | 50 FEET | 100 FEET | 25 FEET | 50 FEET |

SIGN OUTLINE KEY

DASHED OUTLINES INDICATE A SIGN THAT EXISTS ON SITE, AND NEEDS TO BE COVERED.



SOLID OUTLINES INDICATE A SIGN THAT IS TO BE PLACED ON THE PROJECT



NOT TO SCALE



NOT TO SCALE

FILE: 101-GEN-SPACING-CHARTS.dgn

MAINTAINING TRAFFIC TYPICAL

NO: 101-GEN-
SPACING-CHARTS

"B", "D" AND "L" TABLES
CHANNELIZING DEVICE SPACING
SIGN BORDER KEY AND ROLL-AHEAD SPACING

DATE: MAY 2021
SHEET: 2 OF 3

GUIDELINES FOR ROLL-AHEAD DISTANCES FOR TMA VEHICLES – TEST LEVEL 2

| WEIGHT OF TMA VEHICLE | PREVAILING SPEED (POSTED SPEED PRIOR TO WORK ZONE) | ROLL-AHEAD DISTANCE* (DISTANCE FROM FRONT OF TMA VEHICLE TO WORK AREA) |
|-----------------------------|--|--|
| 5.5 TONS (STATIONARY) | 40 MPH OR LESS | 25 FT |

* ROLL-AHEAD DISTANCES ARE CALCULATED USING A 4,410 POUND IMPACT VEHICLE WEIGHT.

GUIDELINES FOR ROLL-AHEAD DISTANCES FOR TMA VEHICLES – TEST LEVEL 3

| WEIGHT OF TMA VEHICLE | PREVAILING SPEED (POSTED SPEED PRIOR TO WORK ZONE) | ROLL-AHEAD DISTANCE* (DISTANCE FROM FRONT OF TMA VEHICLE TO WORK AREA) |
|-----------------------------|--|--|
| 5 TONS (MOBILE) | 45 MPH | 100 FT |
| | 50-55 MPH | 150 FT |
| | 60-75 MPH | 175 FT |
| 12 TONS (STATIONARY) | 45 MPH | 25 FT |
| | 50-55 MPH | 25 FT |
| | 60-75 MPH | 50 FT |

* ROLL-AHEAD DISTANCES ARE CALCULATED USING A 10,000 POUND IMPACT VEHICLE WEIGHT.



NOT TO SCALE

FILE: 101-GEN-SPACING-CHARTS.dgn

MAINTAINING TRAFFIC TYPICAL

NO:

101-GEN-
SPACING-CHARTS

"B", "D" AND "L" TABLES
CHANNELIZING DEVICE SPACING
SIGN BORDER KEY AND ROLL AHEAD SPACING

DATE: MAY 2021
SHEET:

3 OF 3

THE FOLLOWING NOTES APPLY IF CALLED FOR ON THE TRAFFIC TYPICAL

GENERAL NOTES

G1: SEE GEN-SPACING-CHARTS FOR COMMON VALUES INCLUDING:
 D = DISTANCE BETWEEN TRAFFIC CONTROL DEVICES
 L = MINIMUM LENGTH OF TAPER
 B = LENGTH OF LONGITUDINAL BUFFER
 ROLL AHEAD DISTANCE

G2: DISTANCE BETWEEN SIGNS, "D", THE VALUES FOR WHICH ARE SHOWN IN TYPICAL GEN-KEY ARE APPROXIMATE AND MAY NEED ADJUSTING AS DIRECTED BY THE ENGINEER.

G3: ALL TEMPORARY SIGNS, TYPE III BARRICADES, THEIR SUPPORT SYSTEMS AND LIGHTING MUST MEET NATIONAL COOPERATIVE HIGHWAY RESEARCH PROGRAM REPORT 350 (NCHRP 350) TEST LEVEL 3, OR MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) TL-3 AS WELL AS THE CURRENT EDITION OF THE MICHIGAN MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS FOR CONSTRUCTION, THE STANDARD PLANS AND APPLICABLE SPECIAL PROVISIONS. ONLY DESIGNS AND MATERIALS APPROVED BY MDOT WILL BE ALLOWED.

G4: DO NOT STORE EQUIPMENT, MATERIALS OR PERFORM WORK IN ESTABLISHED BUFFER AREAS.

G5: ALL EXISTING PAVEMENT MARKINGS WHICH ARE IN CONFLICT WITH EITHER PROPOSED CHANGES IN TRAFFIC PATTERNS OR PROPOSED TEMPORARY TRAFFIC MARKINGS SHALL BE REMOVED BEFORE ANY CHANGE IS MADE IN THE TRAFFIC PATTERN. EXCEPTION WILL BE MADE FOR TRAFFIC PATTERNS FOR WORK LESS THAN THREE DAYS THAT ARE ADEQUATELY DELINEATED BY OTHER TRAFFIC CONTROL DEVICES.

SIGN NOTES

S1: ALL NON-APPLICABLE SIGNING WITHIN THE CIA MUST BE MODIFIED TO FIT CONDITIONS, COVERED, OR REMOVED. FOR GUIDANCE SEE THE WORK ZONE SAFETY AND MOBILITY MANUAL, SECTIONS 6.01.09 AND 6.01.10.

S2: R5-18b SIGNS ARE ONLY REQUIRED ON FREEWAY PROJECTS WITH A DURATION OF 15 DAYS OR LONGER OR NON-FREEWAY PROJECTS WITH A DURATION OF 90 DAYS OR LONGER. TO APPLY THIS TYPICAL WITHOUT R5-18b SIGNS, REMOVE THE SIGNS AND CONSOLIDATE THE SEQUENCE AS APPROPRIATE.

S3: R5-18c IS ONLY REQUIRED IN THE INITIAL SIGNING SEQUENCE IN THE WORK ZONE. OMIT THIS SIGN IN SUBSEQUENT SEQUENCES IN THE SAME WORK ZONE.

S4: ADDITIONAL SIGNING AND/OR ELONGATED SIGNING SEQUENCES SHOULD BE USED WHEN TRAFFIC VOLUMES ARE SIGNIFICANT ENOUGH TO CREATE BACKUPS BEYOND THE W20-5 SIGNS.

S5: PLACE ADDITIONAL SPEED LIMIT SIGNS REFLECTING THE WORK ZONE SPEED AFTER EACH MAJOR CROSSROAD THAT INTERSECTS THE WORK ZONE, OR AFTER EACH ENTRANCE RAMP THAT COMES ONTO THE FREEWAY WHERE THE REDUCED SPEED IS IN EFFECT. PLACE ADDITIONAL SPEED LIMIT SIGNS AT INTERVALS ALONG THE ROADWAY SUCH THAT NO SPEED LIMIT SIGNS ARE MORE THAN 2 MILES APART. WHEN REDUCED SPEED LIMITS ARE UTILIZED IN THE WORK AREA, PLACE ADDITIONAL SPEED LIMIT SIGNS RETURNING TRAFFIC TO ITS NORMAL SPEED BEYOND THE LIMITS OF THE WORK AREA AS INDICATED. IF PERMANENT SIGNS DISPLAYING THE CORRECT SPEED LIMIT ARE POSTED, OMIT ALL W3-5b AND R2-1 SIGNS AND REDUCE SPACING ACCORDINGLY.

S6: FABRICATE SPECIAL SIGNS IN ACCORDANCE WITH CURRENT SIGNING DESIGN STANDARDS.

S7: PLACE ADDITIONAL R8-3 SIGNS AT A MAXIMUM 500' SPACING THROUGHOUT THE WORK ZONE.

S8: WHEN SPEED LIMIT SIGNS CANNOT BE PLACED SIDE BY SIDE AS SHOWN, PLACE THEM "D" DISTANCE APART.

S9: STOP SIGNS NOT REQUIRED IF SIGNALS ARE ON 4-WAY FLASHING RED. STOP AHEAD SIGNS ARE NOT REQUIRED IF THERE IS ADEQUATE VISIBILITY OF THE STOP SIGN OR IF SIGNALS ARE BEING USED TO CONTROL TRAFFIC.

S10: PLACE REDUCED SPEED ZONE AHEAD SIGN (W3-5b) HERE WHEN USING A SPEED REDUCTION IN THIS DIRECTION.

S11: THE NUMBER OF W1-6 SHIFT SIGNS TO PLACE FOR A SHIFT IS AS FOLLOWS:
 SHIFTS 4FT OR LESS, PLACE ONE W1-6(R)(L)
 SHIFTS 5FT TO 12FT, PLACE TWO W1-6(R)(L)
 SHIFTS MORE THAN 12FT, PLACE THREE OR MORE W1-6(R)(L) SIGNS DEPENDING UPON LENGTH OF SHIFT AND AS PER THE ENGINEER.

S12: PLACE R2-1 SIGNS AS DETAILED IN NOTE S5 WHEN THERE IS A SPEED REDUCTION IN THIS DIRECTION

TRAFFIC REGULATOR NOTES

TR1: TRAFFIC REGULATORS MUST FOLLOW ALL THE REQUIREMENTS IN THE STANDARD SPECIFICATIONS, THE STANDARD PLANS AND APPLICABLE SPECIAL PROVISIONS, THE CURRENT VERSIONS OF THE TRAFFIC REGULATOR'S INSTRUCTION MANUAL AND THE VIDEO "HOW TO SAFELY REGULATE TRAFFIC IN MICHIGAN". THE MAXIMUM DISTANCE BETWEEN THE TRAFFIC REGULATORS IS DETERMINED BY THE ROADWAY ADT, GEOMETRICS, AND AS DIRECTED BY THE ENGINEER.

TR2: PROVIDE APPROPRIATE BALLOON LIGHTING TO SUFFICIENTLY ILLUMINATE TRAFFIC REGULATOR'S STATIONS WHEN TRAFFIC REGULATING IS ALLOWED DURING THE HOURS OF DARKNESS.

TR3: PROVIDE EITHER A STOP/SLOW AFAD OR A RED/YELLOW LENS AFAD, MEETING THE REQUIREMENTS OF THE MMTCD

TEMPORARY TRAFFIC CONTROL DEVICE NOTES

TCD1: THE MAXIMUM DISTANCE IN FEET BETWEEN CHANNELIZING DEVICES IN A TAPER SHOULD NOT EXCEED 1.0 TIMES THE WORK ZONE SPEED LIMIT IN MPH FOR ROADWAYS WITH A POSTED WORK ZONE SPEED LIMIT LESS THAN 45 MPH AND SHOULD NOT EXCEED 50 FEET ON ROADWAYS WITH A POSTED WORK ZONE SPEED LIMIT OF 45 MPH OR GREATER. THE SPACING FOR 42 INCH CHANNELIZING DEVICE TAPERS ARE NOT TO EXCEED 25 FEET AT NIGHT.

TCD2: THE MAXIMUM DISTANCE IN FEET BETWEEN CHANNELIZING DEVICES IN A TANGENT SHOULD NOT EXCEED TWICE THE WORK ZONE SPEED LIMIT IN MPH FOR ROADWAYS WITH A POSTED WORK ZONE SPEED LIMIT LESS THAN 45 MPH AND SHOULD NOT EXCEED 100 FEET ON ROADWAYS WITH A POSTED WORK ZONE SPEED LIMIT OF 45 MPH OR GREATER. THE SPACING FOR 42 INCH CHANNELIZING DEVICE TANGENTS ARE NOT TO EXCEED 50 FEET AT NIGHT.

TCD3: TYPE III BARRICADES MUST BE LIGHTED FOR OVERNIGHT CLOSURES.

TCD4: WHEN THE HAUL ROAD IS NOT IN USE, PLACE LIGHTED TYPE III BARRICADES WITH "ROAD CLOSED" EXTENDING COMPLETELY ACROSS THE HAUL ROAD.

TCD5: USE OBJECT MARKER SIGNS IN LIEU OF THE TYPE B HIGH INTENSITY LIGHT SHOWN IN THE STANDARD PLAN FOR TEMPORARY CONCRETE BARRIER (R-53, AND R-126) WHEN USED WITH A TEMPORARY SIGNAL SYSTEM. THE OBJECT MARKERS MUST BE A MINIMUM OF 12 INCHES IN WIDTH AND 36 INCHES IN HEIGHT AND HAVE ORANGE AND WHITE RETROREFLECTIVE SHEETING. THE RETROREFLECTIVE SHEETING MUST HAVE ALTERNATING DIAGONAL ORANGE AND WHITE STRIPES SLOPING DOWNWARD AT AN ANGLE OF 45 DEGREES IN THE DIRECTION VEHICULAR TRAFFIC IS TO PASS.

TCD6: PLACE LIGHTED ARROW PANELS AS CLOSE TO THE BEGINNING OF TAPERS AS PRACTICAL, BUT NOT IN A MANNER THAT WILL OBSCURE OR CONFUSE APPROACHING MOTORISTS WHEN PHYSICAL LIMITATIONS RESTRICT PLACEMENT. IN CURBED SECTIONS, IF ARROW BOARD CANNOT BE PLACED BEHIND CURB, PLACE ARROW BOARD IN THE CLOSED LANE AS CLOSE TO THE BEGINNING OF TAPER AS POSSIBLE.

TCD7: ADDITIONAL TYPE III BARRICADES MAY BE REQUIRED TO COMPLETELY CLOSE OFF ROAD FROM EDGE OF PAVEMENT TO EDGE OF PAVEMENT.

TCD8: WHERE THE SHIFTED SECTION IS SHORTER THAN 600 FEET, A DOUBLE REVERSE CURVE SIGN (W24-1) CAN BE USED INSTEAD OF THE FIRST REVERSE CURVE SIGN, AND THE SECOND REVERSE CURVE SIGN CAN BE OMITTED.

TCD9: RUMBLE STRIPS ARE TO BE PLACED AS SPECIFIED IN THE CONTRACT. IF NOT SPECIFIED IN THE CONTRACT, PLACE RUMBLE STRIPS AS SHOWN, AND IN ACCORDANCE WITH THE RUMBLE STRIP MANUFACTURER'S RECOMMENDATIONS. AN ARRAY OF RUMBLE STRIPS CONTAINS THREE RUMBLE STRIPS. PLACE THE RUMBLE STRIPS IN THE ARRAY AT A CONSISTENT DISTANCE, BETWEEN 10' AND 20' APART.

TCD10: SEE THE WORK ZONE SAFETY AND MOBILITY MANUAL, PORTABLE CHANGEABLE MESSAGE SIGN GUIDELINES FOR RECOMMENDED AND CORRECT PCMS MESSAGING. STAGGER PCMS THAT ARE ON OPPOSING SIDES OF THE ROAD 1000 FEET FROM EACH OTHER.

RAMP NOTES

RMP1: WHEN CONDITIONS ALLOW, E5-1 SIGNS MUST BE REMOVED OR COVERED AND CHANNELIZING DEVICES MUST BE POSITIONED TO ENABLE RAMP TRAFFIC TO DIVERGE IN A FREE MANNER.

RMP2: STOP AND YIELD CONDITIONS SHOULD BE AVOIDED WHENEVER PRACTICAL. WHEN CONDITIONS WARRANT, R1-1 SIGNS MAY BE USED IN PLACE OF R1-2 SIGNS. WHEN R-1 SIGNS ARE USED, W3-1 SIGNS MUST BE USED IN PLACE OF W3-2 SIGNS. CONSIDERATION SHOULD BE GIVEN TO CLOSING THE RAMP TO COMPLETE WORK TO ALLOW AN ADEQUATE MERGE DISTANCE. WORK SHOULD BE EXPEDITED TO AVOID THE STOP AND/OR YIELD CONDITIONS.



NOT TO SCALE

MAINTAINING TRAFFIC TYPICAL

NO:

102-GEN-NOTES

FILE: 102-GEN-NOTES.dgn

TRAFFIC TYPICALS
NOTE SHEET

DATE: MAY 2022

SHEET:

1 OF 2

THE FOLLOWING NOTES APPLY IF CALLED FOR ON THE TRAFFIC TYPICAL

SIGNAL NOTES

SIG1: EXISTING SIGNAL MUST BE EITHER 4-WAY FLASHING RED, BAGGED, OR TURNED OFF.

SIG2: SIGNAL IS IN OPERATION.

SIG3: DELINEATE THE WORK ZONE AREA WITH 28 INCH CONES FOR DAYTIME WORK, OR 42 INCH CHANNELIZING DEVICES FOR NIGHTTIME WORK.

SIG4: THE CONTRACTOR MUST HAVE A DESIGNATED SPOTTER IF THE AERIAL BUCKET TRUCK IS LOCATED OVER ACTIVE TRAVEL LANES.

SIG5: THE LOWEST POINT OF THE BUCKET MAY NOT TRAVEL BELOW 14 FOOT VERTICAL CLEARANCE. THE CONTRACTOR MUST UTILIZE AN ALTERNATE SET UP, OR PLACE THE INTERSECTION IN A 4 WAY STOP IF THE 14 FOOT VERTICAL CLEARANCE IS COMPROMIZED. USE TRAFFIC REGULATORS TO CONTROL TRAFFIC THROUGH THE INTERSECTION WHEN TRAFFIC IS PLACED IN A 4 WAY STOP.

SIG6: DELINEATE THE TRUCK WITH CHANNELIZING DEVICES. THE POSITION OF THE TRUCK MAY BE MOVED TO FACILITATE WORK.

MAINTENANCE AND SURVEYING NOTES

MS1: WHENEVER STOPPING SIGHT DISTANCE EXISTS TO THE REAR, THE SHADOW VEHICLES SHOULD MAINTAIN THE RECOMMENDED DISTANCE FROM THE WORK AREA AND PROCEED AT THE SAME SPEED. THE SHADOW VEHICLE SHOULD SLOW DOWN AND TRAVEL AT A FARTHER DISTANCE TO PROVIDE ADEQUATE SIGHT DISTANCE IN ADVANCE OF VERTICAL OR HORIZONTAL CURVES.

MS2: WORKERS OUTSIDE OF VEHICLES SHOULD WORK WITHIN 150' OF WORK VEHICLES WITH AN ACTIVATED BEACON, BETWEEN THE "BEGIN WORK CONVOY" SIGN AND THE "END WORK CONVOY" SIGN, OR BETWEEN THE "WORK ZONE BEGINS" AND "END ROAD WORK" SIGN.

MS3: WORK OR SHADOW VEHICLES WITH OR WITHOUT A TMA MAY BE USED TO SEPARATE THE WORK SPACE FROM TRAFFIC. IF USED, THE VEHICLES SHOULD BE PARKED ACCORDING TO THE ROLL AHEAD DISTANCE TABLES.

MS4: WORK AND SHADOW VEHICLES SHALL BE APPROPRIATELY EQUIPPED WITH AN ACTIVATED AMBER BEACON.

MS5: WHEN WORKERS ARE OUTSIDE THEIR VEHICLES IN AN EXISTING LANE WHILE A MOBILE OPERATION IS OCCURRING DURING THE NIGHTTIME HOURS, CHANNELIZING DEVICES TO DELINEATE OPEN OR CLOSED LANES AT 50 FT SPACING MUST BE USED. AN EXAMPLE OF AN OPERATION (BUT NOT LIMITED TO) IS THE LAYOUT OF CONCRETE PATCHES.

MS6: W21-6 AND W20-1 SIGNS MAY BE SUBSTITUTED AS DETERMINED BY THE TYPE OF WORK TAKING PLACE AS PER THE ENGINEER.



NOT TO SCALE

MAINTAINING TRAFFIC TYPICAL

NO:

102-GEN-NOTES

TRAFFIC TYPICALS
NOTE SHEET

DATE:
MAY 2022
SHEET:

2 OF 2

FILE: 102-GEN-NOTES.dgn

SIGN NUMBER KEY



EXIT
E5-1f
48" x 48"
60" x 48"



EXIT OPEN
E5-2
48" x 36"



EXIT CLOSED
E5-2a
48" x 36"



EXIT ONLY
E5-3
48" x 36"




30 MPH
E13-1P
VAR x 24"



20 MPH
E13-1aP
36" x 24"



ROAD WORK
G20-1
60" x 24"



END ROAD WORK
G20-2
48" x 24"



PILOT CAR FOLLOW ME
G20-4
36" x 18"



l-6a
18" x 18"
24" x 24"
30" x 30"



INTERSTATE XX
M1-1
18" x 18"
24" x 24"
36" x 36"
48" x 48"



INTERSTATE XXX
M1-1
22.5" x 18"
30" x 24"
45" x 36"
60" x 48"



BUSINESS XX
M1-2
18" x 18"
24" x 24"
36" x 36"
48" x 48"



BUSINESS XXX
M1-2
22.5" x 18"
30" x 24"
45" x 36"
60" x 48"



BUSINESS XX
M1-3
18" x 18"
24" x 24"
36" x 36"
48" x 48"



BUSINESS XXX
M1-3
22.5" x 18"
30" x 24"
45" x 36"
60" x 48"



XX
M1-4
18" x 18"
24" x 24"
36" x 36"
48" x 48"



XXX
M1-4
22.5" x 18"
30" x 24"
45" x 36"
60" x 48"



MONTGOMERY COUNTY XX
M1-5
18" x 18"
24" x 24"
30" x 30"
36" x 36"



BARAGA COUNTY XXX
M1-5a
18" x 18"
24" x 24"
36" x 36"



BB XX
M1-6
18" x 18"
24" x 24"
36" x 36"



BB XXX
M1-6
22.5" x 18"
30" x 24"
45" x 36"



NORTH
M3-1
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



EAST
M3-2
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



SOUTH
M3-3
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



WEST
M3-4
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



ALTERNATE
M4-1
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



ALT
M4-1a
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



BYPASS
M4-2
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



BUSINESS
M4-3
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



TRUCK
M4-4
18" x 9"
24" x 12"
30" x 15"
36" x 18"



TO
M4-5
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



END
M4-6
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



TEMPORARY
M4-7
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



TEMP
M4-7a
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



DETOUR
M4-8
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



END DETOUR
M4-8a
24" x 18"



END
M4-8b
24" x 12"



DETOUR
M4-9L
30" x 24"
48" x 36"
60" x 48"



DETOUR
M4-9R
30" x 24"
48" x 36"
60" x 48"



DETOUR
M4-9j
30" x 24"
48" x 36"
60" x 48"



DETOUR
M4-9kL
30" x 24"
48" x 36"
60" x 48"



DETOUR
M4-9KR
30" x 30"
48" x 42"
60" x 54"



DETOUR
M4-9mL
30" x 30"
48" x 42"
60" x 54"



DETOUR
M4-9mR
30" x 30"
48" x 42"
60" x 54"



Bicycle
M4-9dL
12" x 18"



Bicycle
M4-9dR
12" x 18"



Bicycle
M4-9e
12" x 18"



END
M4-9f
12" x 18"



END
M4-9gL
12" x 18"



END
M4-9gR
12" x 18"



END
M4-9h
12" x 24"



END
M4-9i
12" x 18"



DETOUR
M4-10L
48" x 18"



DETOUR
M4-10R
48" x 18"



FOLLOW
M4-11a
12" x 6"
18" x 9"
24" x 12"
30" x 15"
36" x 18"



DETOUR
M5-1L
12" x 9"
21" x 15"
30" x 21"



DETOUR
M5-1R
12" x 9"
21" x 15"
30" x 21"



DETOUR
M5-2L
12" x 9"
21" x 15"
30" x 21"



DETOUR
M5-2R
12" x 9"
21" x 15"
30" x 21"



DETOUR
M5-3
12" x 9"
21" x 15"
30" x 21"



DETOUR
M6-1L
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-1R
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-2L
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-2R
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-3
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-4
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-5
12" x 9"
18" x 12"
21" x 15"
30" x 21"




DETOUR
M6-6L
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-6R
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-7L
12" x 9"
18" x 12"
21" x 15"
30" x 21"



DETOUR
M6-7R
12" x 9"
18" x 12"
21" x 15"
30" x 21"

SEE MDOT SHS 13-WORK ZONE FOR SIGN DETAILS



MAINTAINING TRAFFIC TYPICAL

STANDARD HIGHWAY SIGNS

DATE:
10/17/24





CODE:

103-GEN-SIGN

NO SCALE

SHEET:
1 OF 5

SIGN NUMBER KEY

| | | | | | | | |
|--|---|---|--|---|--|---|---|
|  M8-1gL 36" x 66" |  M8-1gR 36" x 66" |  M8-2d 60" x 48" |  OM-3L 12" x 36" 24" x 48" 36" x 72" |  OM-3R 12" x 36" 24" x 48" 36" x 72" |  R1-1 18" x 18" 24" x 24" 30" x 30" 36" x 36" 48" x 48" |  R1-1a 18" x 18" 24" x 24" |  R1-2 18" 24" 30" 36" 48" 60" |
|  R1-2aP 24" x 18" 36" x 30" 48" x 36" |  R2-1 18" x 24" 24" x 30" 30" x 36" 36" x 48" 48" x 60" |  R2-1a 48" x 60" |  R3-1 24" x 24" 30" x 30" 36" x 36" 48" x 48" |  R3-2 24" x 24" 30" x 30" 36" x 36" 48" x 48" |  R3-3 24" x 24" 36" x 36" 48" x 48" |  R3-4 24" x 24" 30" x 30" 36" x 36" 48" x 48" |  R3-5L 30" x 36" 36" x 48" |
|  R3-5R 30" x 36" 36" x 48" |  R3-5a 30" x 36" 36" x 48" |  R3-6L 30" x 36" 42" x 48" |  R3-6R 30" x 36" 42" x 48" |  R3-7L 30" x 30" 36" x 36" |  R3-7R 30" x 30" 36" x 36" |  R3-8c 36" x 30" |  R3-8d 36" x 30" |
|  R4-1 12" x 18" 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R4-2 12" x 18" 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R4-7 12" x 18" 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R4-8 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R4-9 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R5-1 30" x 30" 36" x 36" 48" x 48" |  R5-1a 30" x 18" 36" x 24" 42" x 30" |  R5-18b 48" x 60" |
|  R5-18c 48" x 48" |  R5-18d 78" x 12" |  R5-18e 72" x 12" |  R5-18f 48" x 60" |  R5-18g 30" x 42" |  R5-18h 48" x 60" |  R6-1L 36" x 12" 54" x 18" | |
|  R6-1R 36" x 12" 54" x 18" |  R6-2L 12" x 16" 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R6-2R 12" x 16" 18" x 24" 24" x 30" 36" x 48" 48" x 60" |  R8-3 12" x 12" 18" x 18" 24" x 24" 36" x 36" 48" x 48" |  R9-8 36" x 18" |  R9-9 24" x 12" 30" x 18" |  R9-10 24" x 12" 48" x 24" |  R9-11L 24" x 12" 48" x 36" |
|  R9-11R 24" x 12" 48" x 36" |  R9-11aL 24" x 12" 48" x 24" |  R9-11aR 24" x 12" 48" x 24" |  R10-6b 36" x 54" |  R11-2 48" x 30" |  R11-2a 48" x 30" |  R11-2b 48" x 30" |  R11-2c 60" x 30" |
|  R11-3a 60" x 30" |  R11-3b 60" x 30" |  R11-4 60" x 30" | | | | | |

SEE MDOT SHS 13-WORK ZONE FOR SIGN DETAILS



MAINTAINING TRAFFIC TYPICAL

STANDARD HIGHWAY SIGNS

DATE:

10/17/24

CODE:

103-GEN-SIGN

NO SCALE

SHEET:

2 OF 5

SIGN NUMBER KEY



W1-1L
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-1R
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-2L
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-2R
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-2bL
36" x 36"
48" x 48"



W1-2bR
36" x 36"
48" x 48"



W1-3L
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-3R
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-4L
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-4R
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-4bL
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-4bR
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-4cL
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W1-4cR
24" x 24"
30" x 30"
36" x 36"
48" x 48"



30" x 30"
36" x 36"
48" x 48"



W24-1R
30" x 30"
36" x 36"
48" x 48"



W24-1cP
24" x 18"
30" x 24"



W24-1aL
30" x 30"
36" x 36"
48" x 48"



W24-1aR
30" x 30"
36" x 36"
48" x 48"



W24-1bL
30" x 30"
36" x 36"
48" x 48"



W24-1bR
30" x 30"
36" x 36"
48" x 48"



W1-6L
24" x 12"
36" x 18"
48" x 24"
60" x 30"
96" x 48"



W1-6R
24" x 12"
36" x 18"
48" x 24"
60" x 30"
96" x 48"



W1-8L
12" x 18"
18" x 24"
24" x 30"
30" x 36"
36" x 48"



W1-8R
12" x 18"
18" x 24"
24" x 30"
30" x 36"
36" x 48"



W3-1
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W3-2
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W3-3
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W3-4
30" x 30"
36" x 36"
48" x 48"



W3-4b
30" x 30"
36" x 36"
48" x 48"



W3-5
36" x 36"
48" x 48"



W3-5a
30" x 30"
36" x 36"
48" x 48"



W3-5b
30" x 30"
36" x 36"
48" x 48"



W4-1L
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W4-1R
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W4-2L
30" x 30"
36" x 36"
48" x 48"



W4-2R
30" x 30"
36" x 36"
48" x 48"



W4-3L
30" x 30"
36" x 36"
48" x 48"



W4-3R
30" x 30"
36" x 36"
48" x 48"



W4-5L
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W4-5R
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W4-5P
18" x 24"
24" x 30"



W4-6L
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W4-6R
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W4-7L
30" x 30"
36" x 36"
48" x 48"



W4-7R
30" x 30"
36" x 36"
48" x 48"



W5-1
30" x 30"
36" x 36"
48" x 48"



W5-2
18" x 18"
30" x 30"
36" x 36"
48" x 48"



W5-3
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W5-4
30" x 30"
36" x 36"
48" x 48"



W6-1
30" x 30"
36" x 36"
48" x 48"



W6-2
30" x 30"
36" x 36"
48" x 48"



W6-3
30" x 30"
36" x 36"
48" x 48"



W6-4
12" x 18"



W7-1
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-1
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



SEE MDOT SHS 13-WORK ZONE FOR SIGN DETAILS



MAINTAINING TRAFFIC TYPICAL

STANDARD HIGHWAY SIGNS

DATE:
10/17/24

CODE:

103-GEN-SIGN

NO SCALE

SHEET:
3 OF 5

SIGN NUMBER KEY



W8-2
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-3
18" x 18"
30" x 30"
36" x 36"
48" x 48"



W8-4
18" x 18"
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-5
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-5P
24" x 18"
30" x 24"
36" x 30"
48" x 48"



W8-8
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-9
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-11
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-12
30" x 30"
36" x 36"
48" x 48"



W8-14
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-15
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-15P
24" x 18"
30" x 24"
36" x 30"
48" x 48"



W8-17L
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-17R
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-17P
24" x 18"
30" x 24"
36" x 30"



W8-18
24" x 24"
36" x 36"
48" x 48"



W8-23
24" x 24"
36" x 36"
48" x 48"



W8-24
30" x 30"
36" x 36"
48" x 48"



W8-25
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W8-26
36" x 36"
48" x 48"



W9-1L
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W9-1R
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W9-2L
30" x 30"
36" x 36"
48" x 48"



W9-2R
30" x 30"
36" x 36"
48" x 48"



W9-3C
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W9-3L
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W9-3R
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W9-3a
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W9-3b
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W11-10a
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W11-24
36" x 36"
48" x 48"



W12-1
24" x 24"
30" x 30"
36" x 36"
48" x 48"



W12-2
18" x 18"
30" x 30"
36" x 36"
48" x 48"



W13-1P
18" x 18"
24" x 24"
30" x 30"



W13-2
24" x 30"
36" x 48"
48" x 60"



W13-3
24" x 30"
36" x 48"
48" x 60"



W13-4P
24" x 24"
36" x 36"



W13-6
24" x 42"
36" x 60"
48" x 84"



W13-6a
24" x 42"
36" x 60"
48" x 84"



W13-7
24" x 42"
36" x 60"
48" x 84"



W13-7a
24" x 42"
36" x 60"
48" x 84"



W14-3
36" x 24"
40" x 30"
48" x 36"
64" x 48"



W16-2P
18" x 12"
24" x 18"
30" x 24"
36" x 30"



W16-4aP
18" x 12"
24" x 18"
30" x 24"
36" x 30"



W16-12P
24" x 18"



W16-13P
24" x 18"
30" x 24"



W20-1
24" x 24"
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W20-1a
24" x 24"
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W20-1b
24" x 24"
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W20-1c
24" x 24"
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W20-1d
24" x 24"
30" x 30"
36" x 36"
48" x 48"
60" x 60"



W20-2
30" x 30"
36" x 36"
48" x 48"



W20-3
30" x 30"
36" x 36"
48" x 48"



W20-3a
30" x 30"
36" x 36"
48" x 48"

SEE MDOT SHS 13-WORK ZONE FOR SIGN DETAILS



Michigan Department of Transportation

MAINTAINING TRAFFIC TYPICAL

CODE:

103-GEN-SIGN

STANDARD HIGHWAY SIGNS

DATE:

10/17/24

NO SCALE

SHEET:

4 OF 5

SIGN NUMBER KEY

| | | | | | | | |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| W20-3b 30" x 30" 36" x 36" 48" x 48" | W20-4 30" x 30" 36" x 36" 48" x 48" | W20-4c 36" x 36" 48" x 48" | W20-5C 30" x 30" 36" x 36" 48" x 48" | W20-5L 30" x 30" 36" x 36" 48" x 48" | W20-5L1 30" x 30" 36" x 36" 48" x 48" | W20-5L2 30" x 30" 36" x 36" 48" x 48" | W20-5R 30" x 30" 36" x 36" 48" x 48" |
|  |  |  |  |  |  |  |  |
| W20-5R1 30" x 30" 36" x 36" 48" x 48" | W20-5R2 30" x 30" 36" x 36" 48" x 48" | W20-5aL2 30" x 30" 36" x 36" 48" x 48" | W20-5aL3 30" x 30" 36" x 36" 48" x 48" | W20-5aR2 30" x 30" 36" x 36" 48" x 48" | W20-5aR3 30" x 30" 36" x 36" 48" x 48" | W20-7a 30" x 30" 36" x 36" 48" x 48" | W20-8 24" x 18" |
|  |  |  |  |  |  |  |  |
| W20-9 54" x 48" | W20-10 48" x 24" 66" x 30" | W20-11 12" x 18" | W20-12P VARIABLE x 12" | W20-13P VARIABLE x 12" | W20-14L 36" x 36" 48" x 48" | W20-14R 36" x 36" 48" x 48" | W20-14aP 36" x 12" 48" x 12" |
|  |  |  |  |  |  |  |  |
| W20-14bP 36" x 12" 48" x 12" | W20-15 36" x 36" 48" x 48" | W20-16 36" x 36" 48" x 48" | W20-17 36" x 36" 48" x 48" | W20-18 48" x 54" | W20-18a 48" x 54" | W21-1 24" x 24" 30" x 30" 36" x 36" 48" x 48" | W21-2 24" x 24" 30" x 30" 36" x 36" 48" x 48" |
|  |  |  |  |  |  |  |  |
| W21-2 24" x 24" 30" x 30" 36" x 36" 48" x 48" | W21-3 24" x 24" 30" x 30" 36" x 36" 48" x 48" | W21-4 36" x 18" | W21-5 24" x 24" 30" x 30" 36" x 36" 48" x 48" | W21-5aL 30" x 30" 36" x 36" 48" x 48" 60" x 60" | W21-5aR 30" x 30" 36" x 36" 48" x 48" 60" x 60" | W21-5bL 30" x 30" 36" x 36" 48" x 48" 60" x 60" | W21-5bR 30" x 30" 36" x 36" 48" x 48" 60" x 60" |
|  |  |  |  |  |  |  |  |
| W21-6 24" x 24" 30" x 30" 36" x 36" 48" x 48" | W21-7 30" x 30" 36" x 36" 48" x 48" | W21-8 30" x 30" 36" x 36" 48" x 48" | W22-1 30" x 30" 36" x 36" 48" x 48" | W22-2 42" x 36" | W22-3 36" x 30" 42" x 36" | W23-1 48" x 24" | W23-2 36" x 36" 48" x 48" |

SEE MDOT SHS 13-WORK ZONE FOR SIGN DETAILS



MAINTAINING TRAFFIC TYPICAL

STANDARD HIGHWAY SIGNS

DATE:

10/17/24




CODE:

103-GEN-SIGN

NO SCALE

SHEET:


5 OF 5



NOTE:

ENSURE THE ARROW REMAINS CLEARLY LEGIBLE AT DISTANCES FROM 2,500 FEET TO 200 FEET, FROM ALL TRAFFIC LANES AND ROADWAY ENTRANCES. DO NOT PLACE THE LIGHTED ARROW ON A HORIZONTAL OR VERTICAL CURVE THAT MIGHT INTERFERE WITH THIS LEGIBILITY REQUIREMENT.

| | | | | |
|---|--------------|--|---|---------------------------------------|
|  Michigan Department of Transportation | NOT TO SCALE | MAINTAINING TRAFFIC TYPICAL NO: 104-GEN-AB | USE OF ARROW BOARD ON HILL OR CURVE AND WORK ZONE LAYOUT | DATE: MAY 2021 SHEET: 1 OF 1 |
| | | | | |



KEY

- CHANNELIZING DEVICES
- LIGHTED ARROW PANEL (CAUTION MODE)
- ← TRAFFIC FLOW
- REFLECTS EXISTING SPEED LIMIT
- PLACE SIGN AS INDICATED IN NOTE S2

STANDARD NOTES (SEE 102-GEN-NOTES)

GENERAL: G1, G2, G3, G4
SIGNING: S1, S2, S3, S5
DEVICES: TCD1, TCD2, TCD6, TCD7

SIGN MATERIAL SELECTION TABLE

| SIGN MATERIAL TYPE | | | |
|--------------------------|--------|---------|----------|
| SIGN SIZE | TYPE I | TYPE II | TYPE III |
| ≤ 36" X 36" | | X | X |
| >36" X 36" ≤ 96" TO WIDE | | X | |
| > 96" WIDE TO 144" WIDE | X | X | |
| > 144" WIDE | X | | |

TYPE I ALUMINUM EXTRUSION
 TYPE II PLYWOOD
 TYPE III ALUMINUM SHEET

ROUNDING OF CORNERS IS NOT REQUIRED FOR TYPE I OR II SIGNS.
 VERTICAL JOINTS ARE NOT PERMITTED.
 HORIZONTAL JOINTS THROUGH SIGN LEGEND OR SYMBOLS ARE NOT PERMITTED.


POST SIZE REQUIREMENTS TABLE

| POST TYPE | | | |
|---------------------------------|-----------------|----------------------|--------------|
| SIGN AREA (ft ²) | U-CHANNEL STEEL | SQUARE TUBULAR STEEL | WOOD |
| ≤ 9 | 1 - 3 lb/ft* | 1 - 2" 12 or 14 GA* | N/A |
| 9 ≤ 20 | 2 - 3 lb/ft | 2 - 2" 12 or 14 GA | 1 - 4" X 6"* |
| > 20 ≤ 30 | N/A | N/A | 2 - 4" X 6" |
| > 30 ≤ 60 | N/A | N/A | 2 - 6" X 8" |
| > 60 ≤ 84 | N/A | N/A | 3 - 6" X 8" |


*SIGNS 4 FEET AND GREATER IN WIDTH REQUIRE 2 POSTS.
 SIGNS GREATER THAN 8 FEET IN WIDTH REQUIRE 2 OR 3 WOOD
 POSTS DEPENDING ON AREA OF SIGN.
 A MAXIMUM OF 2 POSTS WITHIN A 7' PATH IS PERMITTED.

| | | |
|--|--|--|
|  PREPARED BY DESIGN DIVISION DRAWN BY: CON/ECH CHECKED BY: AUG | DEPARTMENT DIRECTOR Kirk T. Steudle APPROVED BY: _____ DIRECTOR, BUREAU OF FIELD SERVICES | MICHIGAN DEPARTMENT OF TRANSPORTATION BUREAU OF DEVELOPMENT STANDARD PLAN FOR GROUND DRIVEN SIGN SUPPORTS FOR TEMP SIGNS APPROVED BY: _____ DIRECTOR, BUREAU OF DEVELOPMENT |
| | | F.H.W.A. APPROVAL 11/2/2017 PLAN DATE WZD-100-A SHEET 1 OF 11 |

2 POST SIGN SUPPORT SPACING



3 POST SIGN SUPPORT SPACING



* FOR ALL 11' AND 12' LONG SIGNS ON 3 WOOD SUPPORTS,
SPREAD POSTS SO AS TO HAVE A 8' MIN. TO 9' MAX.
DISTANCE BETWEEN OUTSIDE POSTS.

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN



F.H.W.A. APPROVAL

11/2/2017
PLAN DATE

WZD-100-A

SHEET
2 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.





BOTTOM HEIGHT AND OFFSET

NOT TO SCALE

| | | | | |
|--|-------------------|------------------------|-----------|------------------|
| MICHIGAN DEPARTMENT OF TRANSPORTATION BUREAU OF DEVELOPMENT STANDARD PLAN | F.H.W.A. APPROVAL | 11/2/2017 PLAN DATE | WZD-100-A | SHEET 3 OF 11 |
|--|-------------------|------------------------|-----------|------------------|

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



WEIGHT = 3 lbs/ft
 SECT. MOD. X.-X. = 0.31 CUBIC INCHES MIN.

3 lb. U - CHANNEL STEEL POST
 (NO SPLICE)

MOUNT SIGN ON OPEN FACE OF
 U - CHANNEL STEEL POST

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
 BUREAU OF DEVELOPMENT STANDARD PLAN


F.H.W.A. APPROVAL

11/2/2017
 PLAN DATE

WZD-100-A

SHEET
 4 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



3 lb. U - CHANNEL STEEL POST
(WITH SPLICE)

MOUNT SIGN ON OPEN FACE OF
UPPER U - CHANNEL STEEL POST

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN


F.H.W.A. APPROVAL

11/2/2017
PLAN DATE


WZD-100-A

SHEET
5 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



SECTION A-A



NOTES:

1. THE SPACER THICKNESS SHALL BE 1/16" LESS THAN THE GAP BETWEEN THE POST WHEN POSITIONED IN THE UNBOLTED CONFIGURATION.
2. THE EXTERIOR BOLT (CLOSEST TO LAP), SPACER, WASHER, AND NUT SHALL BE INSTALLED IN A PREPUNCHED HOLE 1" to 2" FROM THE END OF THE LAP.
3. THE INTERIOR BOLT (FARTHEST FROM LAP), SPACER, WASHER, AND NUT SHALL BE INSTALLED IN THE NEXT PREPUNCHED HOLE.
4. THE DRIVEN POST SHALL ALWAYS BE MOUNTED IN FRONT OF THE UPPER POST WITH RESPECT TO THE ADJACENT ONCOMING TRAFFIC, REGARDLESS OF THE DIRECTION THE SIGN IS FACING.
5. THE SPLICE LAP SHALL BE FASTENED BY FOUR-5/16" DIA. GALVANIZED A449 BOLTS (SAE J429 GRADE 5) OR GALVANIZED A325 BOLTS.

3 lb. U - CHANNEL STEEL POST
(WITH SPLICE)

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN


F.H.W.A. APPROVAL

11/2/2017
PLAN DATE


WZD-100-A

SHEET
6 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



SIGN TO 3 lb. POST CONNECTION



NOTES: (FOR STEEL SIGN REINF' PLATE)

1. MATERIAL: 12 GAUGE CARBON STEEL.
2. TOLERANCE ON ALL DIMENSIONS $\pm 0.0625"$
3. FINISH-AFTER STAMPING AND PUNCHING, GALVANIZE ACCORDING TO CURRENT SPECIFICATIONS FOR ZINC (HOT GALVANIZE) COATINGS ON PRODUCTS FABRICATED FROM PLATES OR STRIPS

STEEL SIGN REINFORCING PLATE REQUIRED FOR TYPE III SIGNS ONLY

3 lb. U - CHANNEL STEEL POST SIGN CONNECTION

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN


F.H.W.A. APPROVAL

11/2/2017
PLAN DATE


WZD-100-A

SHEET
7 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



WOOD POST BREAKAWAY HOLES/ DIRECT EMBEDMENT DETAILS




SAW CUT DETAIL (MULTIPLE POST INSTALLATIONS)

WOOD POST DETAILS


NOT TO SCALE

| | | | | |
|--|-------------------|------------------------|-----------|------------------|
| MICHIGAN DEPARTMENT OF TRANSPORTATION BUREAU OF DEVELOPMENT STANDARD PLAN | F.H.W.A. APPROVAL | 11/2/2017 PLAN DATE | WZD-100-A | SHEET 8 OF 11 |
|--|-------------------|------------------------|-----------|------------------|


NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



TYPE II AND TYPE III SIGNS



TOP VIEW
TYPE I SIGN



TYPE I SIGN - ERECTION DETAILS

WOOD POST CONNECTIONS

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN


F.H.W.A. APPROVAL

11/2/2017
PLAN DATE

WZD-100-A

SHEET
9 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



SQUARE TUBULAR STEEL POST

NOT TO SCALE

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF DEVELOPMENT STANDARD PLAN

F.H.W.A. APPROVAL

11/2/2017
PLAN DATE

WZD-100-A

SHEET
10 OF 11

NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.


GENERAL NOTES:

1. A MAXIMUM OF TWO POSTS WITHIN A 7 FOOT PATH IS PERMITTED.
2. ALL SIGN POSTS SHALL COMPLY WITH NCHRP 350.
3. ALL POSTS SHALL BE EMBEDDED A MINIMUM OF 42".
4. BRACING OF POST IS NOT PERMITTED.
5. SIGN SHALL BE LEVEL, AND UPRIGHT FOR THE DURATION OF INSTALLATION.
6. ERECT POSTS SO THE SIGN FACE AND SUPPORTS DO NOT VARY FROM PLUMB BY MORE THAN 3/16" IN 3'. PROVIDE A CENTER-TO-CENTER DISTANCE BETWEEN POSTS WITHIN 2 PERCENT OF PLAN DISTANCE.
7. NO MORE THAN ONE SPLICING PER POST, AS SHOWN, WILL BE PERMITTED.
8. POST TYPES SHALL NOT BE MIXED WITHIN A SIGN SUPPORT INSTALLATION.
9. NO VERTICAL JOINTS ARE PERMITTED IN SIGN. NO HORIZONTAL JOINTS THROUGH SIGN LEGEND OR SYMBOLS ARE PERMITTED IN SIGN
10. REMOVE SIGN POSTS AND/OR POST STUBS IN THEIR ENTIRETY WHEN NO LONGER REQUIRED.
11. ALL LABOR, MATERIALS, AND EQUIPMENT, INCLUDING TEMPORARY SUPPORTS REQUIRED TO INSTALL, MAINTAIN, RELOCATE, AND/OR REMOVE THE TEMPORARY SIGN, INCLUDING SUPPORTS, ARE CONSIDERED TO BE INCLUDED IN THE COST OF THE TEMPORARY SIGN.
12. SAW CUTS IN WOOD POSTS ARE TO BE PARALLEL TO THE BOTTOM OF THE SIGN.
13. POSTS SHALL NOT EXTEND MORE THAN 4" ABOVE TOP OF SIGN.
14. TEMPORARY WOOD SUPPORTS DO NOT REQUIRE PRESERVATIVE TREATMENT.

NOT TO SCALE

| | | | | |
|--|-------------------|------------------------|-----------|-------------------|
| MICHIGAN DEPARTMENT OF TRANSPORTATION BUREAU OF DEVELOPMENT STANDARD PLAN | F.H.W.A. APPROVAL | 11/2/2017 PLAN DATE | WZD-100-A | SHEET 11 of 11 |
|--|-------------------|------------------------|-----------|-------------------|


NOTE: THE ORIGINAL SIGNED COPY IS KEPT ON FILE AT THE MICHIGAN DEPARTMENT OF TRANSPORTATION.



FRONT ELEVATION

SIDE VIEW


PERFORATED SQUARE STEEL TUBE OPTION



FRONT ELEVATION

SIDE VIEW

ANGLE IRON OPTION



LEFT DIRECTIONAL

BI-DIRECTIONAL

RIGHT DIRECTIONAL

CLOSURES

BARRICADE RAIL SHEETING OPTIONS
TYPE III BARRICADES

Other Type III Barricades meeting current NCHRP crash worthy criteria can be found on the FHWA Safety website at
http://safety.fhwa.dot.gov/roadway_dept/road.hardware/wzd.htm

| | |
|--|--|
| MDOT Michigan Department of Transportation | PREPARED BY OPERATIONS FIELD SERVICES |
| | DRAWN BY: <u>ECH</u> |
| CHECKED BY: <u>MWB</u> | |

DEPARTMENT DIRECTOR
Paul C. Ajegba


APPROVED BY: _____
DIRECTOR, BUREAU OF FIELD SERVICES

APPROVED BY: _____
(SPECIAL DETAIL)
DIRECTOR, BUREAU OF HIGHWAY DEVELOPMENT

MICHIGAN DEPARTMENT OF TRANSPORTATION
BUREAU OF FIELD SERVICES SPECIAL DETAIL FOR

Temporary
Traffic Control Devices

| | | | |
|-------------------|---------|-----------|-----------------|
| F.H.W.A. APPROVAL | 6/16/22 | WZD-125-E | SHEET 1 OF 3 |
|-------------------|---------|-----------|-----------------|



SIDE VIEW


FRONT ELEVATION

TEMPORARY SIGN SUPPORT


(WARNING LIGHT PLACED ON SIDE CLOSEST TO TRAFFIC)

* SIGN STAND IS BALLASTED WITH FOUR OR MORE 35 LB SANDBAGS. A MINIMUM OF ONE ON EACH END.

UPRIGHTS SHALL NOT EXTEND ABOVE THE SIGN PANEL.



Z-BRACKET DETAIL




OPTIONAL NYLON WASHER

Other temporary sign supports meeting current NCHRP crash worthy criteria can be found on the FHWA Safety website at

http://safety.fhwa.dot.gov/roadway_dept/road_hardware/wzd.htm

NOT TO SCALE



■ REFLECTORIZED ORANGE
 □ REFLECTORIZED WHITE
 ■■■■■ NON REFLECTORIZED ORANGE

NOTE:
 DRUMS SHALL HAVE AT LEAST 4 HORIZONTAL REFLECTORIZED STRIPES (2 ORANGE AND 2 WHITE) OF 6" UNIFORM WIDTH, ALTERNATING IN COLOR WITH THE TOPMOST REFLECTORIZED STRIPE BEING ORANGE. NON REFLECTORIZED SPACES BETWEEN THE HORIZONTAL REFLECTORIZED ORANGE AND WHITE STRIPES SHALL BE ORANGE IN COLOR AND EQUAL IN WIDTH.

PLASTIC DRUM

NOTES:

2" PERFORATED SQUARE STEEL TUBES MAY BE USED TO FABRICATE THE HORIZONTAL BASE OF THE TYPE III BARRICADE.


WARNING LIGHTS SHALL BE PLACED ACCORDING TO THE CURRENT STANDARD SPECIFICATIONS FOR CONSTRUCTION AND ALL OTHER PROVISIONS IN THE CONTRACT ON TYPE III BARRICADES.

SEE ROAD STANDARD PLANS R-113-SERIES FOR TEMPORARY CROSSOVERS FOR DIVIDED ROADWAY, AND R-126-SERIES FOR TYPICAL LOCATION AND SPACING OF PLASTIC DRUMS FOR PLACEMENT OF TEMPORARY CONCRETE BARRIER.

SIGNS, BARRICADES, AND PLASTIC DRUMS SHALL BE FACED WITH PRESSURE-SENSITIVE REFLECTIVE SHEETING ACCORDING TO THE CURRENT STANDARD SPECIFICATIONS FOR CONSTRUCTION.

SANDBAGS SHALL BE USED WHEN SUPPLEMENTAL WEIGHTS ARE REQUIRED TO ACHIEVE STABILITY OF THE BARRICADE. THE SANDBAGS SHALL BE PLACED SO THEY WILL NOT COVER OR OBSTRUCT ANY REFLECTIVE PORTION OF THE TRAFFIC CONTROL DEVICE.

NOT TO SCALE



R3-2 MOD;

1.50" Radius, 0.44" Border, 0.38" Indent, Black on, White;

"AT", C 2K 80% spacing;

"US-31", C 2K 80% spacing;

MICHIGAN
DEPARTMENT OF TRANSPORTATIONSPECIAL PROVISION
FOR
CONFINED SPACE ENTRY

DET:MS

1 of 1

APPR:MRB:JDG:07-20-21

a. Description. The execution of this project requires "Permit-Required Confined Space Entry" as defined by the MIOSHA Part 35, Part 90 and Part 490. Contractors must submit their corporate health and safety plan, including provisions and procedures for evaluation of confined spaces and permit-required confined space entry to the Engineer prior to the start of work within a confined space. Safety plans must be consistent with all federal, state, and local ordinances and regulations applicable for permit-required confined space entry.

MIOSHA provides direction for permit-required confined space entry requirements, including training and equipment. Details can be found at:

https://www.michigan.gov/documents/lara/lara_miosha_CS_35_504208_7.pdf

- b. Materials.** None specified.
- c. Construction.** None specified.
- d. Measurement and Payment.** The Contractor's cost to complete the work contained herein will not be paid for separately but will be included in the costs for other pay items.

MICHIGAN
DEPARTMENT OF TRANSPORTATION

SPECIAL PROVISION
FOR

GEOPOLYMER SPRAY APPLIED STRUCTURAL LINER FOR JOB NUMBER 217211

STM:JDC

1 of 3

APPR:DMG:MTH:11-10-25

a. Description. This work consists of the design and installation of a spray applied geopolymer liner to structurally rehabilitate an existing concrete box culvert. The work includes cleaning, surface preparation, flow diversion or bypass pumping, debris removal and disposal and reinforcing steel. Ensure the manufacturer of the geopolymer system completes the design, installation and inspection of the liner and has an authorized representative on site during installation.

b. Materials. Furnish a geopolymer mortar composed of a minimum 70 percent pozzolanic material selected from the list of silicon dioxide (SiO_2), magnesium oxide (MgO), aluminum oxide (Al_2O_3), and ferric oxide (Fe_2O_3) and has the minimal properties as shown in Table 1. Ensure the geopolymer composition by X-Ray Fluorescence testing in accordance with *ASTM C114*.

Table 1: Properties of Geopolymer Mortar

| Property | Value | Test Method |
|------------------------|---|--|
| Compressive Strength | 2,500 psi (7 Day) 8,000 psi (28 Day) | <i>ASTM C109/C109M</i> |
| Flexural Strength | 1,500 psi (28 Day) | <i>ASTM C78/C78M</i> |
| Tensile Strength | 800 psi (28 Day) | <i>ASTM C496/C496M</i> |
| Bond Strength | 900 psi (1 day) | <i>ASTM C882/C882M</i> |
| Modulus of Elasticity | 3,000 ksi (1 day) 5,800 ksi (28 day) | <i>ASTM C469/C469M</i> |
| Shrinkage | 0 percent | <i>ASTM C1090/C1090M at 65 percent Relative Humidity</i> |
| Freeze Thaw Durability | 0 percent Loss at 300 Cycles | <i>AASHTO T161</i> |
| Set Time | Initial < 75 min Final < 120 min | <i>ASTM C807</i> |

Furnish Test Data Certification in accordance with the *MQAP Manual* to the Engineer to ensure that all materials meet the requirements specified herein.

Furnish epoxy-coated reinforcing steel in accordance with *ASTM A615/A615M, Grade 60*.

c. Construction. Conduct this work in accordance with the standard specifications, manufacturer's guidelines, the details shown on the plans and as specified herein.

Include Confined Space in Construction training to at least two Department staff members.

Electronically submit the following required documentation to the Engineer for review and approval a minimum of 10 work days prior to starting the work.

1. All design calculations sealed by a Professional Engineer licensed in the State of Michigan. Base the design using a factor of safety of at least 2.0.
2. Detailed construction plans showing reinforcing steel, bar size, spacing, anchors and limits and thickness of geopolymer liner.
3. Chemical analysis report.
4. Written installation plan approved by the manufacturer including flow diversion or bypass pumping, surface preparation, steel placement and spray on liner application.
5. Method to confirm applied liner thickness during installation.
6. Confirmation that applicators are certified by the manufacturer for installation of the geopolymer liner on box culverts of similar size.
7. Certification that the proposed liner is designed for HS-20 loading and will have a design life of at least 50 years.
8. Documentation that Installer has a minimum of 7 years of continuous company experience performing installation of the exact proposed product and has successfully completed at least 25,000 linear feet of 42-inch diameter and larger installations.
9. Documentation that the proposed project superintendent has a minimum of 5 years of experience and has directly supervised installation of at least 7,000 linear feet of 42-inch diameter and larger installations.
10. Ensure the documented experience is company-based and reflects the organization's overall capability, not solely the qualifications of newly hired personnel. Applicators who employ an individual superintendent to meet these requirements but lack the requisite company experience will not be considered qualified.

Do not begin work until approval is received from the Engineer.

Clean all sides and prepare the internal surface of the existing concrete box culvert with high pressure spray water to remove silt, debris and delaminated concrete. Furnish and employ a means to capture and collect debris and broken concrete from the cleaning operation from leaving the site. Brush and remove loose exposed steel reinforcement. Dispose of all debris in accordance with the standard specifications.

After cleaning and before beginning the lining process, inspect the existing culvert surface for holes or obstructions that would hinder the lining process. Patch holes and gaps in the existing culvert surface with an approved hydraulic cement or the same geopolymer material to be used for the liner to create a solid and smooth continuous surface on which to spray on the liner. Eliminate water infiltration by applying hydraulic cement, filling holes with polyurethane foam, injecting chemical acrylamide grout or other methods approved by the Engineer. Video survey the culvert after surface preparation and patching is complete and furnish a copy of the video to the Engineer.

Install reinforcing steel and anchoring in accordance with the details shown on the plans and

subsection 706.03.E of the Standard Specifications for Construction. Furnish anchor adhesive from the QPL (713.02B).

Install the geopolymer liner in accordance with the manufacturer's guidelines. Apply the geopolymer liner to the prepared surface to the thickness as shown on the plans using methods that create a uniform surface following the manufacturer's installation plan. Use only equipment recommended by the manufacturer.

Collect six cylinders of geopolymer material for testing for each work day for batches less than or equal to 25,000 pounds. Three are for compressive strength testing at 7 days after casting the material and three are for compressive strength testing at 28 days after casting the material. Collect an additional set of six cylinders for each work day for each additional 25,000 pound batch. Conduct testing in accordance with *ASTM C39/C39M* using 4 inch by 8 inch cylinders.

Confirm the required applied thickness using gauge screws locations as determined by the Engineer at least once every 5 feet longitudinally and every 3 feet vertically. Ensure gauge screws are installed on all four internal sides of the culvert. Apply additional material to any areas found to be less than the required thickness.

Conduct post construction video inspection of the culvert after completion of the liner installation and furnish a copy of the video to the Engineer.

Ensure the finished geopolymer liner is continuous over the entire length of the culvert and is free from visual defects, such as foreign inclusions and cracks. Correct any deficiency noted by the Engineer utilizing a method approved by the manufacturer. Complete all required corrective actions at no cost to the contract.

Furnish a certification, sealed by a Professional Engineer licensed in the State of Michigan, ensuring that the geopolymer liner has been designed and installed in accordance with the applicable *ASTM* standards and this special provision.

Remove flow diversion or bypass pumping materials and equipment when no longer needed.

d. Measurement and Payment. The completed work, as described, will be measured as a lump sum and paid for at the contract price using the following pay item:

| Pay Item | Pay Unit |
|----------------------------------|----------|
| Geopolymer Structural Liner..... | Lump Sum |

Furnish all labor, equipment and materials necessary to complete the work as described. Confined Space Training will be included in this pay item and will not be paid for separately.

MICHIGAN
DEPARTMENT OF TRANSPORTATIONSPECIAL PROVISION
FOR
SLOPE RESTORATION, NON-FREEWAY

RSD:NJM

1 of 3

APPR:DMG:KJK:08-19-25

a. Description. This work consists of preparing all lawns and slopes on non-freeway projects designated for slope restoration on the plans or as directed by the Engineer and applying topsoil, fertilizer, seed, mulch with mulch anchor, mulch blanket, high velocity mulch blanket, permanent turf reinforcement mat, bonded fiber matrix, or modified mulch blanket to those areas. Ensure turf establishment is in accordance with section 816 and 917 of the Standard Specifications for Construction and Standard Plan R-100 Series, except as modified herein or otherwise directed by the Engineer.

b. Materials. The materials, application rates, and construction methods specified in sections 816 and 917 of the Standard Specifications for Construction apply unless modified by this special provision or otherwise directed by the Engineer. Furnish the following materials on this project:

1. Seeding mixture as called for on the plans.
2. Chemical fertilizer nutrient, Class B.
3. Topsoil. The following percentages of furnished and salvaged topsoil are estimated for this project and provided for informational purposes only.

Topsoil Furnished: 100 percent

4. Mulching materials.

c. Construction. Ensure construction methods are in accordance with subsection 816.03 of the Standard Specifications for Construction. Begin this work as soon as possible after final grading of the areas shown on the plans for slope restoration but no later than the time limitations in accordance with subsection 208.03.B of the Standard Specifications for Construction. It may be necessary, as directed by the Engineer, to place materials by hand.

Shape, compact, and ensure all areas to be seeded are weed-free prior to placing topsoil. Place topsoil to the minimum depth of 4 inches and in accordance with the plans and standard specifications to meet proposed finished grade. If the area being restored requires more than the minimum depth of topsoil to meet finished grade, fill this additional depth using topsoil or, at the Contractor's option, embankment. Furnishing and placing this additional material is included in this item of work for slope restoration.

Ensure topsoil is weed and weed seed free and friable prior to placing seed. Remove any stones greater than 1/2-inch in diameter or other debris. Apply seed mixture and fertilizer to prepared soil surface at the specified rates. Incorporate seed into top 1/2-inch of topsoil.

Spread mulch at a rate of two tons per acre. If the Engineer allows dormant seeding spread mulch at a rate of 3 tons per acre. Place mulch anchoring over the mulch at a rate in accordance with subsection 816.03.F of the Standard Specifications for Construction. Place mulch blanket and high-velocity mulch blanket in accordance with subsection 816.03.G of the Standard Specifications for Construction and Standard Plan R-100 Series.

Install areas constructed with the TRM on prepared (seeded) grades as shown on the plans in accordance with the manufacturer's published installation guidelines. Anchor the top edge of the TRM in a minimum six-inch deep trench. Operation of equipment on the slope is prohibited after placement of the TRM. No credit for splices, overlaps, tucks, or wasted material will be made.

Mix the BFM and organic binders thoroughly at a rate of 40 pounds for each 100 gallons of water or as otherwise recommended by the manufacturer. Hydraulically apply the BFM slurry in successive layers, from two or more directions, to fully cover 100 percent of the soil surface. Ensure the minimum application rate is at least 3000 pounds of BFM for each acre or otherwise apply in accordance with the manufacturer's recommendations as appropriate depending on site conditions.

Do not apply BFM on saturated soil or immediately before, during, or after rainfall.

Install modified mulch blanket in accordance with the manufacturer's published guidelines and as directed by the Engineer.

If an area washes out after this work has been properly completed and approved by the Engineer, make the required corrections to prevent future washouts and replace the topsoil, fertilizer, seed, and mulch treatment. This replacement will be paid for as additional work using the applicable pay items.

If an area washes out for reasons attributable to the Contractor's activity or failure to take proper precautions, replacement will be at no cost to the contract.

The Engineer will inspect the seeded turf to ensure it is well-established, in a vigorous growing condition, contains the species called for in the seeding mixture and acceptance is in accordance with subsection 816.03.K of the Standard Specifications for Construction.

If the seeded turf is not well-established at the end of the first growing season, the Contractor must reseed as detailed herein until the turf is well established and approved by the Engineer at no cost to the contract.

Provide weed control, if weeds are determined by the Engineer to cover more than 10 percent of the total area of slope restoration, in accordance with subsection 816.03.I of the Standard Specifications for Construction. Weed control will be at no additional cost to the contract.

d. Measurement and Payment. The completed work, as described, will be measured and paid for at the contract unit price using the following pay items:

| Pay Item | Pay Unit |
|--|-------------|
| Slope Restoration, Non-Freeway, Type _____ | Square Yard |

1. Place **Slope Restoration, Non-Freeway, Type A** in all areas not described in the other types of slope restoration and will be measured by area in square yards in place. **Slope Restoration, Non-Freeway, Type A** includes installing Topsoil Surface; Fertilizer, Chemical Nutrient; seeding mixture; Mulch; and Mulch Anchoring.

UTILITIES STATUS REPORT

| CONTROL SECTION(S) 24011 | | JOB NUMBER(S) 217211 | | | | | | | |
|-------------------------------------|------------------|----------------------------|----|---|----|--|----|-----------------------------------|----|
| UTILITY | FACILITY TYPE | RELOCATION WORK IDENTIFIED | | UTILITY TO RELOCATE PRIOR TO START DATE | | COORDINATION INFORMATION IN CONTRACT DOCUMENTS | | UTILITY WORK INCLUDED IN CONTRACT | |
| | | YES | NO | YES | NO | YES | NO | YES | NO |
| AT&T | Telecom | | ✓ | | | | ✓ | | ✓ |
| Charter Communications | Telecom | | ✓ | | | | ✓ | | ✓ |
| City of Petoskey (Primary; 3-phase) | Electric, Lights | | ✓ | | | | ✓ | | ✓ |
| City of Petoskey | Sanitary Sewer | | ✓ | | | | ✓ | | ✓ |
| City of Petoskey | Water | | ✓ | | | | ✓ | | ✓ |
| DTE Gas | Gas | | ✓ | | | | ✓ | | ✓ |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

ONE OF THE FOLLOWING SHALL BE CHECKED:

The above is a list of utilities which have indicated they have facilities in the project area. Coordination arrangements, if necessary, have been made and are noted in the Notice to Bidders and/or Special Provisions documents.


The above is a list of utilities which have indicated they have facilities in the project area. There are no known utility adjustments required by this project.

There are utilities within the project area. However based upon the project's limited scope of work, no utility impacts are anticipated. Utility information has not been solicited for this project and does not need to be listed above.

| | |
|---|------------------|
| NAME Kimberly Mikula - Utility Coordinator | DATE 07/31/24 |
| OFFICE MDOT - Gaylord TSC | |

MICHIGAN DEPARTMENT OF TRANSPORTATION

ROUTE: US-31 RESORT TOWNSHIP EMMET COUNTY



| SECTION | CONTROL SEC | JOB NO. | FED AID PROJ |
|---------|-------------|---------|--------------|
| 1 & 2 | 24011 | 217211A | NO |


TRAFFIC DATA

| ROAD | YEAR | SPEED DATA | | | | | |
|-----------|------|------------|-------|------|--------|--------|--------------------------|
| | | ADT | DHV | COMM | DESIGN | POSTED | LIMITS |
| EPPLER RD | 2023 | 1,508 | 151 | 4% | 30 | 25 | US-31 TO W SHERIDAN RD |
| | 2043 | 1,667 | 167 | 4% | 30 | 25 | |
| US-31 | 2023 | 15,776 | 1,578 | 4% | 55 | 50 | RESORT PIKE TO EPPLER RD |
| | 2043 | 17,431 | 1,743 | 4% | 55 | 50 | |
| US-31 | 2023 | 12,970 | 1,297 | 4% | 45 | 40 | EPPLER RD TO JACKSON ST |
| | 2043 | 14,331 | 1,433 | 4% | 45 | 40 | |



CULV-055379 OF 24011
US-31 AT EPPLER
STR #: CULV-055379
JN: 217211

PROPOSED CULVERT REHABILITATION
STA: US-31 393+68.15
PR #: 1164305
PR MP: 5.567



NOTES:

EXCEPT WHERE OTHERWISE INDICATED IN THE PROPOSAL AND
SUPPLEMENTAL SPECIFICATIONS CONTAINED HEREIN, PERFORM
ALL WORK ACCORDING TO THE MICHIGAN DEPARTMENT OF
TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION
2020 EDITION.

MILES:

CONTRACT FOR:
CULVERT REHABILITATION AT US-31, WEST OF EPPLER RD, INCLUDES
CULVERT LINING AND MAINTENANCE OF TRAFFIC.

BRADLEY C. WIEFERICH, P.E. - DIRECTOR



NO SCALE

FILE: 217211_EPPLER_CULVERT_TITLE.DGN

DESIGN UNIT: RADULSKI

TSC: GAYLORD

DATE: 12/8/25

CS: 24011

TITLE

DRAWING SHEET

JN: 217211

US-31 AT EPPLER RD CULVERT REHABILITATION

EPPLER

SECT 1
TITLE
001

PROJECT LOG

GLD: CLB
12-10-25

1 of 3

CS 24011
JN 217211

PROJECT LOCATION

The project is located on US-31 adjacent to the west of Eppler Road, located in Resort Township, Emmet County. The culvert (CULV-055379 of 24011) crosses US-31 at the location described below.

| <u>DESCRIPTION</u> | <u>STATION</u> | <u>PRMP</u> | <u>PR#</u> |
|--------------------|----------------|-------------|------------|
| US-31 Centerline | 393+68.15 | 5.567 | 1164305 |

GENERAL INFORMATION

The portion of the culvert to be worked on is of concrete box construction ranging from 6.5-feet to 8-feet wide by 4-feet high. For more details see the *General Plan of Site* and *General Plan of Structure*.

DESCRIPTION OF WORK AND DETAILS

The rehabilitation work includes installing Geopolymer Spray Applied Structural Liner, as shown in plans.

TRAFFIC CONTROL

Traffic will be maintained as described in the *Special Provision for Maintaining Traffic*, and/or as directed by the Engineer.

GENERAL NOTES

UTILITIES

Miss Dig/Underground Utility Notification

Contact MISS DIG System, Inc. for the protection of underground utilities and in conformance with MCL 460.721 et seq, by phone at 811 or 800-482-7171 or via the web at <http://www.missdig811.org/>, a minimum of 3 working days prior to excavating, excluding weekends and holidays.

SURVEY

Preserve all corners within the project limits, whether shown or not. Adjust monument boxes as required.

OLD PLANS

Old Road Plans

The following old road plans were referred to in the design of this project.

JN 00307A, 00308A, 03822A (1971)
Drainage Improvements and Roadway Recon
CS F24011, U24011, Mrp15012

JN 110605, 113598, 121492 (2015)
HMA Crush & Shape, Reconstruction, and Safety

EARTHWORK

Soil Erosion Measures

Place appropriate soil erosion and sedimentation control measures prior to earth-disturbing activities. Place turf establishment items as soon as possible on potential erodible slopes as directed by the Engineer. Protect critical ditch grades with either sod or seed/mulch or mulch blanket as directed by the Engineer.

TURF ESTABLISHMENT

Use symbol TDS for the permanent turf seed mixture.

PROJECT SPECIFIC NOTES

BICYCLISTS AND PEDESTRIAN FACILITIES

Alternate facilities for bicyclists and pedestrians (including those with disabilities in accordance with the Americans with Disabilities Act of 1990) must be provided in places where the work zone impacts their accessibility.

CONFINED SPACE ENTRY

Perform work in accordance with special provision for Confined Space Entry when access is required within the existing box culvert, and as required by the Contractor's means and methods.

CULVERT ACCESS

The Contractor can access downstream of the culvert for delivery of materials. Any other access will be the Contractor's responsibility to coordinate with the property owner.

EXISTING CULVERT CONDITIONS

Before placing its bid, the Contractor is encouraged to review the Video Inspection and Photos. A copy of the video inspection and photos can be reviewed at the MDOT Gaylord TSC, by contacting Matt Radulski at 989-745-3783. The Contractor should familiarize itself with the existing general, local, and site conditions that may affect cost, progress, and performance of the work.

PROPERTY ACCESS

Access to businesses/properties must be maintained at all times throughout the construction of the project.

PROJECT QUANTITIES. The following items of work will be used as directed by the Engineer, and are **for information only**. These items are not detailed or included on the log sheets.

| Mainline Work Items | Quantity | Unit |
|--|-----------------|-------------|
| Mobilization, Max. | 1 | LSUM |
| Erosion Control, Silt Fence | 25 | Ft |
| Slope Restoration, Non-Freeway, Type A | 25 | Syd |
| Geopolymer Structural Liner | 1 | LSUM |
| Contractor Staking | 1 | LSUM |
| Staking Plan Errors and Extras, Max \$180/hour | 7 | Hr |

| Maintaining Traffic Items | Quantity | Unit |
|--|-----------------|-------------|
| Barricade, Type III, High Intensity, Single Sided, Lighted, Furn | 4 | Ea |
| Barricade, Type III, High Intensity, Single Sided, Lighted, Oper | 4 | Ea |
| Pedestrian Type II Barricade, Temp | 2 | Ea |
| Connected Arrow Board, Type C, Furn | 1 | Ea |
| Connected Arrow Board, Type C, Oper | 1 | Ea |
| Minor Traf Devices | 1 | LSUM |
| Plastic Drum, Fluorescent, Furn | 30 | Ea |
| Plastic Drum, Fluorescent, Oper | 30 | Ea |
| Sign Cover | 2 | Ea |
| Sign, Type B, Temp, Prismatic, Furn | 265 | Sft |
| Sign, Type B, Temp, Prismatic, Oper | 265 | Sft |
| Sign, Type B, Temp, Prismatic, Spec, Furn | 47 | Sft |
| Sign, Type B, Temp, Prismatic, Spec, Oper | 47 | Sft |

SURVEY

GENERAL
 △ ALIGNMENT POINT MONUMENT
 @ MONUMENT BOX

CONTROL
 △ CP CONTROL POINT
 ▲ BENCHMARK
 △ REFERENCE - GPS
 + REFERENCE - NGS
 REFERENCE - USGS

BOUNDARY



GENERAL LABELING

GENERAL
 LEFT TURN ARROW
 RIGHT TURN ARROW
 TRAFFIC FLOW ARROW



VEGETATION

BRUSH LINE
 HEDGE LINE
 TREE LINE - CANOPY OR TRUNK
 TRUNK LINE

SHRUB
 TREE - CONIFER
 TREE - DECIDUOUS
 TREE - STUMP

ENVIRONMENTAL

EROSION CONTROL - SILT FENCE
 WETLAND - LEGAL
 CONTAMINATION - MONITORING WELL
 EROSION CONTROL NUMBER
 EROSION CONTROL - RIPRAP
 WATER TABLE - PLAN NOTE
 WETLAND - SPOT EL.
 POTENTIALLY CONTAMINATED SITE

CONSTRUCTION LIMITS

—ss— —ss— SLOPE STAKE LINE

ROADSIDE / SITE

ANTENNA
 BIG ROCK
 FLAG POLE
 PICNIC STOVE
 PICNIC TABLE
 SATELLITE DISH

MONUMENT PRESERVATION

PRESERVE PRESERVE MONUMENT
PROTECT PROTECT MONUMENT



NO SCALE

CS: 24011
 JN: 217211

LEGEND
 US-31 AT EPPLER RD CULVERT REHABILITATION

DRAWING SHEET
 LEGEND SECT 1
 001


NOTE:

EXISTING ITEMS ARE REPRESENTED BY THIN LINE WEIGHTS.
 PROPOSED ITEMS ARE REPRESENTED BY HEAVIER LINE WEIGHTS.

S01 OF 12345
 STRUCTURE NO. + CONTROL SEC. LABEL

LITTLE TRAVERSE WHEELWAY US-31

z



LITTLE TRAVERSE WHEELWAY







US-31




| | | | | | | | | | | | | |
|--|----------------|------------|-----------|--------------|-----------------------|-----|---|---------------------------------------|-----------|--------|---------------|-----|
|  Michigan Department of Transportation | DATE: 11/14/25 | | CS: 24011 | | JN: 217211 | | US-31 AT EPPLER RD CULVERT REHABILITATION | | ALIGNMENT | | DRAWING SHEET | |
| | 0 | HORZ. (FT) | 150 | TSC: GAYLORD | DESIGN UNIT: RADULSKI | 150 | 0 | FILE: 217211_Eppler_Culvert_Align.dgn | EPPLER | SECT 1 | ALL | 001 |

LITTLE TRAVERSE BAY

LITTLE TRAVERSE WHEELWAY





SURVEY CONTROL & BENCHMARKS


SEE SURVEY INFORMATION SHEET FOR SURVEY CONTROL
AND BENCHMARKS

UTILITIES

SEE THE UTILITY STATUS REPORT FOR UTILITIES

EXISTING CULVERT

THE EXISTING CULVERT CONSISTS OF A 6.5' X 4' REINFORCED CONCRETE BOX, AN 8' X 4' REINFORCED CONCRETE BOX CULVERT.



PROFILE ALONG US-31 LEGAL ALI

HORIZONTAL SCALE 1" = 20'

PLAN

NOTES:

THE WORK COVERED BY THESE PLANS INCLUDE REHABILITATION OF THE EXISTING BOX CULVERT.


(1) THE LOWER LOCATION IS 6.5 X 4'. REHABILITATION INCLUDES INSTALLING A GEOPOLYMER STRUCTURAL LINER.

(2) THE MIDDLE LOCATION IS 8' X 4'. REHABILITATION INCLUDES
INSTALLING GEOPOLYMER STRUCTURAL LINER.


(3) THE TOP LOCATION IS 8' X 4'. REHABILITATION INCLUDES INSTALLING A GEOPOLYMER STRUCTURAL LINER..

MAINTAIN TRAFFIC OVER THE CULVERT ON US-31.

| GENERAL PLAN OF SITE | | | | DRAWING SHEET |
|---|-----------------------|---------------|----------------|---------------|
| US-31 AT EPPLER RD CULVERT REHABILITATION | | | | SECT 1 |
| MDOT | | CULV SITE 001 | | |
| Michigan Department of Transportation | | | | |
| FILE: 217211_Eppler_Site.dgn | | | | |
| 0 | VERT. (FT) | 20 | DATE: 12/10/25 | CS: 24011 |
| 0 | DESIGN UNIT: RADULSKI | | JN: 2117211 | |
| 0 | HORZ. (FT) | 160 | TSC: GAYLORD | |



| MDOT | | GENERAL PLAN OF STRUCTURE | | DRAWING SHEET |
|---------------------------------------|------------|---|-----------|----------------|
| Michigan Department of Transportation | | US-31 AT EPPLER RD CULVERT REHABILITATION | | CULV GPSTR 001 |
| FILE: 217211_Eppler_gpstr.dgn | | DATE: 1/21/05 | CS: 24011 | |
| DESIGN UNIT: RADULSKI | JN: 217211 | | | |
| TSC: GAYLORD | | | | |
| 0 | HORZ. (FT) | 60 | | |



 MDOT Michigan Department of Transportation
FILE:217211_EPPLER_GPSTR_02.DG

| GENERAL PLAN OF STRUCTURE | | | | DRAWING SHEET |
|--|-----------|------------|------------|-----------------------|
| US-31 AT EPPLER RD CULVERT REHABILITATION | | | | SECT 2 |
| | | | | CULV GPSTR 002 |
|  MDOT <small>Michigan Department of Transportation</small> | CS: 24011 | | | |
| | | | JN: 217211 | |
| FILE: 217211_EPPLER_GPSTR_02.DGN | 0 | VERT. (FT) | 30 | DATE: 1/21/05 |
| | 0 | HORZ. (FT) | 60 | DESIGN UNIT: RADULSKI |
| | | | | TSC: GAYLORD |

BID SHEET

Board of Emmet County Road Commissioners
2265 East Hathaway Road
Harbor Springs, MI 49740

The undersigned proposes to furnish any and all materials, labor, and equipment necessary for the Culvert Rehabilitation at US-31, West of Eppler Rd, Includes Culvert Lining and Maintenance of Traffic. as spelled out in the "Invitation to Bid" for the prices below.

The Emmet County Road Commission and MDOT reserves the right to reject any and/or all bids based on what is in the best interest of Emmet County and MDOT.

Contractor Name: _____

Project:
US-31 Eppler Culvert Lining

Project Quantities:

Quantities are provided in the Proposal and are for informational purposes only. The Contractor is responsible for verifying the work items and quantities. No additional compensation will be paid for increases in quantities or additional incidental items necessary to complete the work. All completed work will be measured and paid as one lump sum.

Build America/Buy America Act:

This project is subject to The Build America, Buy America Act requires that all of the iron, steel, manufactured products, and construction materials used in infrastructure projects are produced in the United States.

TOTAL LUMP SUM BID: _____

Bidder: _____ Address: _____

Signature: _____ Phone No.: _____

Printed Name: _____ Date: _____

Title: _____ Email: _____